



Material Safety Data Sheet

Page 1 of 5

<u>Supplier</u>	Manufacturer
Acco Brands Corporation	J. Penner Corp.
300 Tower Parkway	17 Weldon Road
Lincolnshire, Il 60069	Doylestown, PA 18901
Telephone: 800-541-0094	Telephone: 215-340-9700
FAX: 800-247-1317	FAX: 215-340-9704

Supplier Emergency Contact & Phone Number

1. Product and Company Identification

None Given

Manufacturer Emergency Contact & Phone Number

InfoTrac: 800-535-5053

Issue Date: 12/10/07

Website: www.Acco.com

Product Name: Quartet Board Gear Marker Board Cleaner

Chemical Family: Semi Viscous Mixture

MSDS Number: 021599A

Revision: 14

Product Part Number: 551

Ingredient Name	CAS Number	Percentage of Total Weight
Kaopolite	1392076-7	< 25 %
Siltech	06314-86-29	< 10 %
Odorless Mineral Spirits	64741-65-7	< 25 %
d-Limonene	5989-27-5	< 10 %
Butylated Hydroxy Toluene	128-37-0	< 1 %
Deionized Water	7735-18-5	> 50 %

3. Hazards Identification

Routes of Entry

Inhalation, Skin, Eye, Ingestion

Acute Health Hazards

Based on the information available for ingredients, this product may cause minor to moderate eye and skin irritation. Product may be harmful if inhaled or swallowed

Chronic Health Hazards

None Known

Reproductive Hazards

None Known





Material Safety Data Sheet

Page 2 of 5

3. Hazards Identification - Continued

Sensitization to Material

Product is not known to cause allergies

Medical Conditions Aggravated by Exposure

None Reported

Synergistic Materials

None Known

4. First Aid Measures

Inhalation

Remove victim to fresh air. If breathing difficulty does not improve rapidly, get patient to a doctor.

<u>Skin</u>

Wash skin with mild soap and water. Rinse thoroughly. See a doctor if irritation persists.

Eyes

Flush with plenty of water for at least 15 minutes. Get medical attention immediately

<u>Ingestion</u>

Do not induce vomiting. Obtain medical attention immediately.

For further health information, contact the Rocky Mountain Poison Control Center at 1-303-739-1110.

5. Fire Fighting Measures

Flash Point: Tag Closed Cap – 120 °F (48.8 °C)

Auto Ignition Point: N/A Lower Explosive Limit: N/A Upper Explosive Limit: N/A

Fire and Explosion Hazards

Product contains approximately 25% ingredients with flash point of 120 °F. It will not burn after the water has evaporated, residue might be a fire hazard.

Extinguishing Media

Not Applicable

Fire Fighting Instructions

Not Applicable

6. Accidental Release Information

Use protective equipment to avoid skin contact. Spills can be cleaned up with vermiculite or other flammable absorbent material and removed to an approved disposal container. Do not hose spills down drains. Move leaking containers to well ventilated area. Avoid inhalation. Avoid ignition sources.





Material Safety Data Sheet

Page 3 of 5

7. Handling and Storage

Handling and Storage Precautions

Store in cool, dry area. Avoid sources of ignition. Protect containers from physical damage.

8. Exposure Controls / Personal Protection

Engineering Controls

Local or mechanical ventilation recommended.

Eye/Face Protection

Chemical splash goggles are recommended

Skin Protection

Neoprene gloves are recommended. Protective clothing as required by work place standards.

Respiratory Protection

Normally not required

Other / General Protection

Wash hands thoroughly after handling. Have eyewash and safety shower readily available.

9. Physical and Chemical Properties

Appearance

Semi-viscous, creamy white liquid

<u>Odor</u>

Petroleum citrus odor

Melting Point: N/A

Boiling Point: 210 – 225 °F **Specific Gravity:** 1.0

Ph: Neutral

Vapor Pressure: N/A **Vapor Density:** N/A

Solubility: Yes, miscible. Product contains water.

Evaporation Rate: N/A





Material Safety Data Sheet

Page 4 of 5

10. Stability and Reactivity

Stability: Stable

Hazardous Polymerization: Will not occur

Incompatible Materials

None

Hazardous Decomposition Products

Oxides of carbon

11. Toxicology Information

This material has been tested and evaluated by J. Penner Corporation. When used as intended, it does not represent a health or safety hazard.

	Kaolin	OSHA PEL	ACGIH TLV	LC ₅₀ ppm (Inhalation, rat)	LD ₅₀ mg/kg (Oral, rat)
Kaopolite					
Calcined Kaolin	Respirable	5.0 mg/m^3	5 mg/m^3		
Clay AL ₂ O ₃ 2SiO ₂	Total Dust	10.0 mg/m^3	10 mg/m^3		
Siltech		N.E.	N.E.	N.E.	N.E.
Odorless Mineral Spirits		100 PPM	100 PPM	592 PPM/4H	25 ML/KG
d-Limonene		N/A	N/A	N/A	N/A
Deionized Water		N/A	N/A	N/A	N/A

12. Ecological Information

No data available

13. Disposal Considerations

Dispose in accordance with applicable federal, state, and local regulations.

14. Transportation Information

Proper Shipping Name: N/A **Hazard Class:** Non-Hazardous

DOT Identification Number: None Required **DOT Shipping Label:** None Required





Material Safety Data Sheet

Page 5 of 5

15. Regulatory Information

SARA Hazardous Classes

None

<u>Ingredient(s) – U.S. Regulatory Information</u>

None

16. Other Information

HMIS Rating

Health: 1 Fire: 0 Reactivity: 0 PPE: None

Disclaimer

Although the information and recommendations set forth herein (hereinafter "information") are presented in good faith and believed to be correct as of the date hereof J. Penner Corporation makes no representations as to the completeness or accuracy thereof. Information is provided upon the condition that the persons receiving same will make their own determination as to its suitability for their purposes prior to use. In no event will J. Penner Corporation be responsible for damages of any nature whatsoever resulting from use of or reliance upon said information. NO REPRESENTATIONS OR WARRANTIES, EITHER EXPRESSED OR IMPLIED, OF MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE OR OF ANY OTHER NATURE ARE MADE HEREUNDER WITH RESPECT TO INFORMATION OR THE PRODUCT TO WHICH INFORMATION REFERS.