

## Naked Gun Spray Gun Paint Remover

Printed: 04/17/2015

Revision: 04/17/2015

Supersedes Revision: 03/20/2015

## 1. PRODUCT AND COMPANY IDENTIFICATION

<b>Product Name:</b>	Naked Gun Spray Gun Paint Remover	
<b>Company Name:</b>	W. M. Barr 2105 Channel Avenue Memphis, TN 38113	<b>Phone Number:</b> (901)775-0100
<b>Web site address:</b>	www.wmbarr.com	
<b>Emergency Contact:</b>	3E 24 Hour Emergency Contact	(800)451-8346
<b>Information:</b>	W.M. Barr Customer Service	(800)398-3892
<b>Intended Use:</b>	Removes both solvent and waterborne paints from hard to reach areas	
<b>Synonyms:</b>	ENG11131	
<b>Additional Information</b>	This product is regulated by the United States Consumer Product Safety Commission and is subject to certain labeling requirements under the Federal Hazardous Substances Act. These requirements differ from the classification criteria and hazard information required for safety data sheets (SDS). The product label also includes other important information, including directions for use, and should always be read in its entirety prior to using the product.	

## 2. HAZARDS IDENTIFICATION

Flammable Aerosols, Category 1  
 Gas Under Pressure, Liquefied gas  
 Acute Toxicity: Oral, Category 4  
 Acute Toxicity: Skin, Category 4  
 Acute Toxicity: Inhalation, Category 4  
 Skin Corrosion/Irritation, Category 2  
 Serious Eye Damage/Eye Irritation, Category 2A  
 Germ Cell Mutagenicity, Category 1A  
 Carcinogenicity, Category 1B  
 Specific Target Organ Toxicity (single exposure), Category 1  
 Aspiration Toxicity, Category 1  
 Simple Asphyxiant



**GHS Signal Word:** Danger

**GHS Hazard Phrases:**

- H223: Flammable aerosol.
- H280: Containers gas under pressure; may explode if heated.
- H302: Harmful if swallowed.
- H304: May be fatal if swallowed and enters airways.
- H312: Harmful in contact with skin.
- H315: Causes skin irritation.
- H319: Causes serious eye irritation.
- H332: Harmful if inhaled.
- H340: May cause genetic defects.
- H350: May cause cancer.
- H370: Causes damage to organ.

**GHS Precaution Phrases:**

- P201: Obtain special instructions before use.
- P202: Do not handle until all safety precautions have been read and understood.
- P210: Keep away from heat/sparks/open flames/hot surfaces. - No smoking.
- P211: Do not spray on an open flame or any other ignition source.
- P251: Pressurized container: Do not pierce or burn, even after use.

## Naked Gun Spray Gun Paint Remover

Printed: 04/17/2015

Revision: 04/17/2015

Supersedes Revision: 03/20/2015

## GHS Response Phrases:


P260: Do not breathe gas/mist/vapors/spray.  
 P264: Wash hands thoroughly after handling.  
 P270: Do not eat, drink or smoke when using this product.  
 P271: Use only outdoors or in a well-ventilated area.  
 P280: Wear protective gloves/protective clothing/eye protection/face protection.  
 P281: Use personal protective equipment as required.  
 P301+310: IF SWALLOWED: Immediately call a POISON CENTER or doctor/physician.  
 P312: Call a POISON CENTER or doctor/physician if you feel unwell.  
 P302+352: IF ON SKIN: Wash with plenty of soap and water.  
 P304+340: IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing.  
 P305+351+338: IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.  
 P307+311: IF exposed: Call a POISON CENTER or doctor/physician.  
 P308+313: IF exposed or concerned: Get medical attention/advice.  
 P321: Specific treatment see label.  
 P322: Specific measures label.  
 P330: Rinse mouth.  
 P331: Do NOT induce vomiting.  
 P332+313: If skin irritation occurs, get medical advice/attention.  
 P337+313: If eye irritation persists, get medical advice/attention.  
 P362: Take off contaminated clothing and wash before re-use.  
 P363: Wash contaminated clothing before reuse.

## GHS Storage and Disposal Phrases:

P405: Store locked up.  
 P410+403: Protect from sunlight and store in well-ventilated place.  
 P412: Do not expose to temperatures exceeding 50 °C/122 °F.  
 P501: Dispose of contents/container according to local, state and federal regulations.

## Hazard Rating System:

HEALTH	*	2
FLAMMABILITY		4
PHYSICAL		0
PPE		X



## HMIS:

## OSHA Regulatory Status:

This material is classified as hazardous under OSHA regulations.

## Potential Health Effects (Acute and Chronic):

## INHALATION EFFECTS:

Vapor harmful. High concentrations of this material may lead to central nervous system effects, such as dizziness, headaches, nausea, drowsiness, paralysis, loss of consciousness, and even death. May cause watering and irritation of the eyes, nose, throat, and lungs. May cause irritation of the respiratory tract. Other effects may include nasal discharge, hoarseness, coughing, chest pain, and breathing difficulty.

Repeated or prolonged exposure to solvents may cause liver and kidney damage.

Intentional misuse of this product by deliberately concentrating and inhaling can be harmful or fatal.

## SKIN EFFECTS:

Repeated or prolonged contact with the skin can result in defatting and drying of the skin which may result in skin irritation and dermatitis. Symptoms may include redness, burning, drying, cracking of the skin, and burning of the skin. Skin contact may aggravate an existing dermatitis condition. May be absorbed through the skin.

## EYE CONTACT EFFECTS:

## Naked Gun Spray Gun Paint Remover

Printed: 04/17/2015

Revision: 04/17/2015

Supersedes Revision: 03/20/2015

Contact with the eyes may cause moderate to severe irritation. May cause slight to moderate corneal injury. Effects may include discomfort, pain, tearing, stinging, watering of the eyes, redness, and/or change of vision. Vapors may cause eye irritation, seen as mild discomfort and redness.

## INGESTION EFFECTS:

Danger! Poison. Harmful if swallowed. Product may be harmful or fatal if swallowed. Pulmonary aspiration hazard. After ingestion, may enter lungs and produce damage. May produce central nervous system effects, which may include dizziness, loss of balance and coordination, unconsciousness, coma and even death. Irritating to the mouth, throat, and stomach.

**Medical Conditions Generally Aggravated By Exposure:** Preexisting disorders and conditions of the following organs, or organ systems, may be aggravated by exposure to this material: skin, lungs, liver, kidney, central nervous system, pancreas, heart, chronic lung disease, coronary artery diseases, or anemias.

## 3. COMPOSITION/INFORMATION ON INGREDIENTS

CAS #	Hazardous Components (Chemical Name)	Concentration	RTECS #
67-64-1	Acetone {2-Propanone}	40.0 -70.0 %	AL3150000
68476-86-8	Liquified petroleum gas, sweetened {propane, isobutane, n-butane}	<20.0 %	NA
67-56-1	Methanol {Methyl alcohol; Carbinol; Wood alcohol}	10.0 -20.0 %	PC1400000
1330-20-7	Xylene (mixed isomers) {Benzene, dimethyl-}	< 9.0 %	ZE2100000
111-76-2	Ethanol, 2-Butoxy- {Ethylene glycol n-butyl ether, (a glycol ether)}	<10.0 %	KJ8575000
108-65-6	Propylene glycol methyl ether acetate (PMA glycol ether acetate)	< 1.0 %	AI8925000
78-93-3	Methyl ethyl ketone {MEK; 2-Butanone}	< 5.0 %	EL6475000
100-41-4	Ethylbenzene {Ethylbenzol; Phenylethane}	< 3.0 %	DA0700000
95-63-6	1,2,4-Trimethylbenzene {Pseudocumene}	< 2.0 %	DC3325000
620-14-4	Benzene, 1-Ethyl-3-methyl- {3-Ethyltoluene}	< 2.0 %	NA
98-82-8	Cumene {Benzene, 1-Methylethyl; Isopropylbenzene}	< 1.0 %	GR8575000

**Additional Chemical Information** Specific percentage of composition is being withheld as a trade secret.

# SAFETY DATA SHEET

## Naked Gun Spray Gun Paint Remover

Page: 4

Printed: 04/17/2015

Revision: 04/17/2015

Supersedes Revision: 03/20/2015

### 4. FIRST AID MEASURES

#### Emergency and First Aid Procedures:

##### Skin:

Remove contaminated clothing. Immediately wash skin thoroughly with large amounts of water and mild soap, if available. Seek medical attention if irritation develops or persists.

##### Eyes:

Immediately begin to flush eyes with water, remove any contact lens. Continue to flush the eyes for at least 15 minutes. Seek medical attention.

##### Inhalation:

Remove to fresh air. If not breathing, give artificial respiration. If breathing is difficult, give oxygen. Get immediate medical attention.

##### Ingestion:

If swallowed, do NOT induce vomiting. Seek immediate medical attention. Call a physician or poison control center immediately. Never give anything by mouth to an unconscious person.

#### Signs and Symptoms Of Exposure:

See Potential Health Effects.

#### Note to Physician:

This product contains methanol which can cause intoxication and central nervous system depression. Methanol is metabolized to formic acid and formaldehyde. These metabolites can cause metabolic acidosis, visual disturbances and blindness. Since metabolism is required for these toxic symptoms, their onset may be delayed from 6 to 30 hours following ingestion. Ethanol competes for the same metabolic pathway and has been used to prevent methanol metabolism. Ethanol administration is indicated in symptomatic patients or at blood methanol concentrations above 20 ug/dl. Methanol is effectively removed by hemodialysis.

### 5. FIRE FIGHTING MEASURES

#### Flash Pt:

Level 3 Aerosol

No data.

#### Explosive Limits:

LEL: 1.8 % UEL: 12.8 %

#### Autoignition Pt:

No data.

**Suitable Extinguishing Media:** Dry chemical, CO2, alcohol-resistant foam or water spray.

#### Unsuitable Extinguishing Media:

None known.

#### Fire Fighting Instructions:

As in any fire, wear self-contained breathing apparatus pressure-demand, MSHA/NIOSH approved or equivalent) and full protective gear.

Self-contained respiratory protection should be provided for fire fighters fighting fires in buildings or confined areas.

Storage containers exposed to fire should be kept cool with water spray to prevent pressure build-up.

Stay away from heads of containers that have been exposed to intense heat or flame. Containers can build up pressure if exposed to heat (fire).

#### Flammable Properties and Hazards:

EXTREMELY FLAMMABLE.

Flashpoint of liquid concentrate: ~10 F (SCC)

Flashpoint of propellant: -142.5 F (closed cup)

# SAFETY DATA SHEET

## Naked Gun Spray Gun Paint Remover

Page: 5

Printed: 04/17/2015

Revision: 04/17/2015

Supersedes Revision: 03/20/2015

### Flammability Classification:

## 6. ACCIDENTAL RELEASE MEASURES

**Steps To Be Taken In Case Material Is Released Or Spilled:** Keep unnecessary people away; isolate hazard area and deny entry. Stay upwind, out of low areas, and ventilate closed spaces before entering. Shut off ignition sources; keep flares, smoking or flames out of hazard area.

Small Spills: take up liquid with sand, earth or other noncombustible absorbent material and place in a plastic container where applicable.

Large Spills: dike far ahead of spill for later disposal.

## 7. HANDLING AND STORAGE

**Precautions To Be Taken in Handling:** Danger! Contents under pressure. Do not puncture or incinerate. "Empty" containers retain product residue (liquid and/or vapor) and can be dangerous. DO NOT PRESSURIZE, CUT, WELD, BRAZE, SOLDER, DRILL, GRIND, OR EXPOSE SUCH CONTAINERS TO HEAT, FLAME, SPARKS, STATIC ELECTRICITY, OR OTHER SOURCES OF IGNITION. THEY MAY EXPLODE AND CAUSE INJURY OR DEATH. Empty drums should be completely drained, properly bunged and promptly returned to a drum reconditioner, or properly disposed of.

Keep away from sources of ignition. Ground and bond containers when transferring material.

**Precautions To Be Taken in Storing:** Keep container closed when not in use. Do not store in direct sunlight. Store in a tightly closed container. Store in cool, dry area.

## 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

CAS #	Partial Chemical Name	OSHA TWA	ACGIH TWA	Other Limits
67-64-1	Acetone {2-Propanone}	PEL: 1000 ppm	TLV: 500 ppm STEL: 750 ppm	No data.
68476-86-8	Liquified petroleum gas, sweetened {propane, isobutane, n-butane}	No data.	No data.	No data.
67-56-1	Methanol {Methyl alcohol; Carbinol; Wood alcohol}	PEL: 200 ppm	TLV: 200 ppm STEL: 250 ppm	No data.
1330-20-7	Xylene (mixed isomers) {Benzene, dimethyl-}	PEL: 100 ppm	TLV: 100 ppm STEL: 150 ppm	No data.
111-76-2	Ethanol, 2-Butoxy- {Ethylene glycol n-butyl ether, (a glycol ether)}	PEL: 50 ppm	TLV: 20 ppm	No data.
108-65-6	Propylene glycol methyl ether acetate (PMA glycol ether acetate)	No data.	No data.	No data.
78-93-3	Methyl ethyl ketone {MEK; 2-Butanone}	PEL: 200 ppm	TLV: 200 ppm STEL: 300 ppm	No data.
100-41-4	Ethylbenzene {Ethylbenzol; Phenylethane}	PEL: 100 ppm	TLV: 100 ppm STEL: 125 ppm	No data.
95-63-6	1,2,4-Trimethylbenzene	No data.	No data.	No data.

# SAFETY DATA SHEET

## Naked Gun Spray Gun Paint Remover

Page: 6

Printed: 04/17/2015

Revision: 04/17/2015

Supersedes Revision: 03/20/2015

{Pseudocumene}

620-14-4	Benzene, 1-Ethyl-3-methyl- {3-Ethyltoluene}	No data.	No data.	No data.
98-82-8	Cumene {Benzene, 1-Methylethyl-; Isopropylbenzene}	PEL: 50 ppm	TLV: 50 ppm	No data.

**Respiratory Equipment  
(Specify Type):**

A respiratory protection program that meets OSHA's 29 CFR 1910.134 and ANSI Z88.2 requirements must be followed whenever workplace conditions warrant a respirator's use.

**Eye Protection:**

If the work area is not properly ventilated to keep airborne levels below their exposure limits, you must use a properly fitted and maintained NIOSH approved respirator for organic vapors. A dust mask does not provide protection against vapors.

Safety glasses, chemical goggles, or face shields are recommended to safeguard against potential eye contact, irritation, or injury. Chemical goggles or face shields are recommended when splashing or spraying of chemical is possible. A faceshield provides more protection to help reduce chemical contact to the face and eyes.

**Protective Gloves:**

Wear gloves with as much resistance to the chemical ingredients as possible. Laminate film gloves offer the best protection. Other glove materials such as nitrile may provide protection. Glove selection should be based on chemicals being used and conditions of use. Consult your glove supplier for additional information. Gloves contaminated with product should be discarded and not reused.

**Other Protective Clothing:**

Various application methods can dictate the use of additional protective safety equipment, such as impermeable aprons to minimize exposure.

**Engineering Controls  
(Ventilation etc.):**

Use only with adequate ventilation to prevent the buildup of vapors. Do not use in areas where vapors can accumulate and concentrate. Whenever possible, use outdoors in an open air area. If using indoors, open all windows and doors and maintain a cross ventilation of moving fresh air across the work area away from the individual. If strong odor is noticed or you experience slight dizziness, headache, nausea, or other signs of inhalation exposure, STOP. The ventilation is inadequate. Leave the area immediately.

Use process enclosures, local exhaust ventilation, or other engineering controls to control airborne levels below recommended exposure limits.

**Work/Hygienic/Maintenance  
Practices:**

A source of clean water should be available in the work area when handling this product. Wash hands thoroughly after use and before eating, drinking, or smoking. Do not eat, drink, or smoke in the work area. Discard any clothing or other protective equipment that cannot be decontaminated.

# SAFETY DATA SHEET

## Naked Gun Spray Gun Paint Remover

Page: 7

Printed: 04/17/2015

Revision: 04/17/2015

Supersedes Revision: 03/20/2015

### 9. PHYSICAL AND CHEMICAL PROPERTIES

**Physical States:** ☒ Gas ☒ Liquid ☐ Solid

**Appearance and Odor:** Liquid, mobile, free and clear.

**Melting Point:** No data.

**Boiling Point:** No data.

**Autoignition Pt:** No data.

**Flash Pt:** No data.

**Explosive Limits:** LEL: 1.8 % UEL: 12.8 %

**Specific Gravity (Water = 1):** 0.808

**Density:** 6.755 LB/GL

**Vapor Pressure (vs. Air or mm Hg):** 29.45 MM HG at 68.0 F

**Vapor Density (vs. Air = 1):** > 1

**Evaporation Rate:** > 1

**Solubility in Water:** partially

**Percent Volatile:** 100.0 %

**VOC / Volume:** < 50.0000 % WT

### 10. STABILITY AND REACTIVITY

**Stability:** Unstable ☐ Stable ☒

**Conditions To Avoid - Instability:** No data available.

**Incompatibility - Materials To Avoid:** Chromic anhydride, chromyl alcohol, hexachloromelamine, hydrogen peroxide, permonosulfuric acid, potassium tertbutoxide, and thioglycol. Strong oxidizers and acids. Nitric acid, sulfuric acid. Avoid contact with reactive metals, such as aluminum and magnesium.

**Hazardous Decomposition Or Byproducts:** Combustion may produce carbon monoxide, carbon dioxide, and other asphyxiants.

**Possibility of Hazardous Reactions:** Will occur ☐ Will not occur ☒

**Conditions To Avoid - Hazardous Reactions:** No data available.

# SAFETY DATA SHEET

## Naked Gun Spray Gun Paint Remover

Page: 8

Printed: 04/17/2015

Revision: 04/17/2015

Supersedes Revision: 03/20/2015

### 11. TOXICOLOGICAL INFORMATION

<b>Toxicological Information:</b>	<p>Product has not been tested as a whole. Refer to section 2 for acute and chronic effects.</p> <p>CAS# 67-64-1:</p> <p>Standard Draize Test, Eyes, Species: Rabbit, 20.00 MG, Severe.</p> <p>Result:</p> <p>Behavioral: Change in motor activity (specific assay).</p> <p>Behavioral: Alteration of classical conditioning.</p> <p>- American Journal of Ophthalmology., Ophthalmic Pub. Co., 435 N. Michigan Ave., Suite 1415, Chicago, IL 60611, Vol/p/yr: 29,1363, 1946</p> <p>CAS# 1330-20-7:</p> <p>Acute toxicity, LC50, Inhalation, Rat, 5000. PPM, 4 H.</p> <p>Result:</p> <p>Behavioral: Muscle contraction or spasticity.</p> <p>Lungs, Thorax, or Respiration:Other changes.</p> <p>- Raw Material Data Handbook, Vol.1: Organic Solvents, 1974., National Assoc. of Printing Ink Research Institute, Francis McDonald Sinclair Memorial Labor, Lehigh Univ., Bethlehem, PA 18015, Vol/p/yr: 1,123, 1974</p> <p>Standard Draize Test, Eyes, Species: Rabbit, 5.000 MG, 24 H, Severe.</p> <p>Result:</p> <p>Behavioral: General anesthetic.</p> <p>Behavioral: Somnolence (general depressed activity).</p> <p>Behavioral: Irritability.</p> <p>- "Sbornik Vysledku Toxixologickeho Vysetreni Latek A Pripravku," , Institut Pro Vychovu Vedoucicn P, Marhold, J.V., Institut Pro Vychovu Vedoucicn, Pracovniku Chemickeho, Prumyclu Praha Czechoslovakia, Vol/p/yr: -,24, 1972</p> <p>CAS# 111-76-2:</p> <p>Acute toxicity, LC50, Inhalation, Rat, 450.0 PPM, 4 H.</p> <p>Result:</p> <p>Behavioral: Ataxia.</p> <p>Nutritional and Gross Metabolic:Weight loss or decreased weight gain.</p> <p>- Toxicology and Applied Pharmacology, Academic Press, Inc., 1 E. First St., Duluth, MN 55802, Vol/p/yr: 68,405, 1983</p> <p>Acute toxicity, LD50, Skin, Species: Rabbit, 220.0 MG/KG.</p> <p>Result:</p> <p>Effects on Embryo or Fetus: Extra embryonic structures (e.g., placenta, umbilical cord).</p> <p>Effects on Embryo or Fetus: Other effects to embryo.</p> <p>Specific Developmental Abnormalities: Musculoskeletal system.</p> <p>- Dow Chemical Company Reports., Dow Chemical USA, Health and Environment Research, Toxicology Research Lab, Midland, MI 48640, Vol/p/yr: MSD-46,</p> <p>Acute toxicity, LD50, Oral, Rat, 250.0 mg/kg.</p> <p>Result:</p> <p>Lungs, Thorax, or Respiration:Changes in pulmonary vascular resistance.</p> <p>Standard Draize Test, Eyes, Species: Rabbit, 100.0 MG, Severe.</p> <p>Result:</p>
-----------------------------------	---



## Naked Gun Spray Gun Paint Remover

Printed: 04/17/2015

Revision: 04/17/2015

Supersedes Revision: 03/20/2015

Effects on Newborn: Apgar score (human only).

Effects on Newborn: Other neonatal measures or effects.

Effects on Newborn: Drug dependency.

- American Journal of Ophthalmology., Ophthalmic Pub. Co., 435 N. Michigan Ave.,  
Suite 1415, Chicago, IL 60611, Vol/p/yr: 29,1363, 1946

CAS# 78-93-3:

Standard Draize Test, Eyes, Human, 350.0 PPM.

Result:

Behavioral: Anticonvulsant.

- Journal of Industrial Hygiene and Toxicology, Vol/p/yr: 25,282, 1943

CAS# 100-41-4:

Tumorigenic Effects:, TCLo, Inhalation, Rat, 750.0 ppm.

Result:

Tumorigenic: Carcinogenic by RTECS criteria.

Kidney, Ureter, Bladder: Tumors.

Standard Draize Test, Eyes, Species: Rabbit, 500.0 MG, Severe.

Result:

Effects on Fertility: Post-implantation mortality (e.g., dead and/or resorbed implants per total number of implants).

Effects on Fertility: Litter size (e.g.; # fetuses per litter; measured before birth).

Effects on Embryo or Fetus: Fetotoxicity (except death, e.g., stunted fetus).

- American Journal of Ophthalmology., Ophthalmic Pub. Co., 435 N. Michigan Ave.,  
Suite 1415, Chicago, IL 60611, Vol/p/yr: 29,1363, 1946

**Carcinogenicity/Other  
Information:**

IARC 3: Not Classifiable as to Carcinogenicity in Humans.

IARC 2B - Possibly Carcinogenic to Humans

ACGIH A3 - Confirmed Animal Carcinogen with Unknown Relevance to Humans

ACGIH A4 - Not Classifiable as a Human Carcinogen.

CAS #	Hazardous Components (Chemical Name)	NTP	IARC	ACGIH	OSHA
67-64-1	Acetone {2-Propanone}	n.a.	n.a.	A4	n.a.
68476-86-8	Liquified petroleum gas, sweetened {propane, isobutane, n-butane}	n.a.	n.a.	n.a.	n.a.
67-56-1	Methanol {Methyl alcohol; Carbinol; Wood alcohol}	n.a.	n.a.	n.a.	n.a.
1330-20-7	Xylene (mixed isomers) {Benzene, dimethyl-}	n.a.	3	A4	n.a.
111-76-2	Ethanol, 2-Butoxy- {Ethylene glycol n-butyl ether, (a glycol ether)}	n.a.	3	A3	n.a.
108-65-6	Propylene glycol methyl ether acetate (PMA glycol ether acetate)	n.a.	n.a.	n.a.	n.a.
78-93-3	Methyl ethyl ketone {MEK; 2-Butanone}	n.a.	n.a.	n.a.	n.a.
100-41-4	Ethylbenzene {Ethylbenzol; Phenylethane}	n.a.	2B	A3	n.a.
95-63-6	1,2,4-Trimethylbenzene {Pseudocumene}	n.a.	n.a.	n.a.	n.a.
620-14-4	Benzene, 1-Ethyl-3-methyl- {3-Ethyltoluene}	n.a.	n.a.	n.a.	n.a.
98-82-8	Cumene {Benzene, 1-Methylethyl-; Isopropylbenzene}	n.a.	2B	n.a.	n.a.

# SAFETY DATA SHEET

## Naked Gun Spray Gun Paint Remover

Page: 10  
Printed: 04/17/2015  
Revision: 04/17/2015  
Supersedes Revision: 03/20/2015

### 12. ECOLOGICAL INFORMATION

**General Ecological Information:** Product has not been tested as a whole.

### 13. DISPOSAL CONSIDERATIONS

**Waste Disposal Method:** Dispose of in accordance with all applicable local, state, and federal regulations.

### 14. TRANSPORT INFORMATION

**LAND TRANSPORT (US DOT):**

**DOT Proper Shipping Name:** Aerosols, flammable  
**DOT Hazard Class:** 2.1 FLAMMABLE GAS  
**UN/NA Number:** UN1950



**Additional Transport Information:** The shipper / supplier may apply one of the following exceptions: Combustible Liquid, Consumer Commodity, Limited Quantity, Viscous Liquid, Does Not Sustain Combustion, or others, as allowed under 49CFR Hazmat Regulations. Please consult 49CFR Subchapter C to ensure that subsequent shipments comply with these exceptions.

### 15. REGULATORY INFORMATION

**EPA SARA (Superfund Amendments and Reauthorization Act of 1986) Lists**

CAS #	Hazardous Components (Chemical Name)	S. 302 (EHS)	S. 304 RQ	S. 313 (TRI)
67-64-1	Acetone {2-Propanone}	No	Yes 5000 LB	No
68476-86-8	Liquified petroleum gas, sweetened {propane, isobutane, n-butane}	No	No	No
67-56-1	Methanol {Methyl alcohol; Carbinol; Wood alcohol}	No	Yes 5000 LB	Yes
1330-20-7	Xylene (mixed isomers) {Benzene, dimethyl-}	No	Yes 100 LB	Yes
111-76-2	Ethanol, 2-Butoxy- {Ethylene glycol n-butyl ether, (a glycol ether)}	No	No	Yes-Cat. N230
108-65-6	Propylene glycol methyl ether acetate (PMA glycol ether acetate)	No	No	Yes-Cat
78-93-3	Methyl ethyl ketone {MEK; 2-Butanone}	No	Yes 5000 LB	No
100-41-4	Ethylbenzene {Ethylbenzol; Phenylethane}	No	Yes 1000 LB	Yes
95-63-6	1,2,4-Trimethylbenzene {Pseudocumene}	No	No	Yes
620-14-4	Benzene, 1-Ethyl-3-methyl- {3-Ethyltoluene}	No	No	No
98-82-8	Cumene {Benzene, 1-Methylethyl-; Isopropylbenzene}	No	Yes 5000 LB	Yes

**This material meets the EPA 'Hazard Categories' defined for SARA Title III Sections 311/312 as indicated:**

<input checked="" type="checkbox"/> Yes	<input type="checkbox"/> No	Acute (immediate) Health Hazard
<input checked="" type="checkbox"/> Yes	<input type="checkbox"/> No	Chronic (delayed) Health Hazard
<input checked="" type="checkbox"/> Yes	<input type="checkbox"/> No	Fire Hazard
<input checked="" type="checkbox"/> Yes	<input type="checkbox"/> No	Sudden Release of Pressure Hazard
<input type="checkbox"/> Yes	<input checked="" type="checkbox"/> No	Reactive Hazard

## Naked Gun Spray Gun Paint Remover

Printed: 04/17/2015

Revision: 04/17/2015

Supersedes Revision: 03/20/2015

CAS #	Hazardous Components (Chemical Name)	Other US EPA or State Lists
67-64-1	Acetone {2-Propanone}	CAA HAP,ODC: No; CWA NPDES: No; TSCA: Yes - Inventory, 4 Test; CA PROP.65: No
68476-86-8	Liquified petroleum gas, sweetened {propane, isobutane, n-butane}	CAA HAP,ODC: No; CWA NPDES: No; TSCA: Yes - Inventory; CA PROP.65: No
67-56-1	Methanol {Methyl alcohol; Carbinol; Wood alcohol}	CAA HAP,ODC: HAP; CWA NPDES: No; TSCA: Yes - Inventory; CA PROP.65: Yes
1330-20-7	Xylene (mixed isomers) {Benzene, dimethyl-}	CAA HAP,ODC: HAP; CWA NPDES: Yes; TSCA: Yes - Inventory; CA PROP.65: No
111-76-2	Ethanol, 2-Butoxy- {Ethylene glycol n-butyl ether, (a glycol ether)}	CAA HAP,ODC: HAP; CWA NPDES: No; TSCA: Yes - Inventory; CA PROP.65: No
108-65-6	Propylene glycol methyl ether acetate (PMA glycol ether acetate)	CAA HAP,ODC: HAP; CWA NPDES: No; TSCA: Yes - Inventory, 8A PAIR, 8D TERM; CA PROP.65: No
78-93-3	Methyl ethyl ketone {MEK; 2-Butanone}	CAA HAP,ODC: No; CWA NPDES: No; TSCA: Yes - Inventory; CA PROP.65: No
100-41-4	Ethylbenzene {Ethylbenzol; Phenylethane}	CAA HAP,ODC: HAP; CWA NPDES: Yes; TSCA: Yes - Inventory, 4 Test; CA PROP.65: Yes
95-63-6	1,2,4-Trimethylbenzene {Pseudocumene}	CAA HAP,ODC: No; CWA NPDES: No; TSCA: Yes - Inventory; CA PROP.65: No
620-14-4	Benzene, 1-Ethyl-3-methyl- {3-Ethyltoluene}	CAA HAP,ODC: No; CWA NPDES: No; TSCA: No; CA PROP.65: No
98-82-8	Cumene {Benzene, 1-Methylethyl-; Isopropylbenzene}	CAA HAP,ODC: HAP; CWA NPDES: No; TSCA: Yes - Inventory, 4 Test; CA PROP.65: Yes

## 16. OTHER INFORMATION

Revision Date: 04/17/2015

Preparer Name: W.M. Barr EHS Dept (901)775-0100

Additional Information About No data available.

This Product:

Company Policy or

Disclaimer:

The information contained herein is presented in good faith and believed to be accurate as of the effective date shown above. This information is furnished without warranty of any kind. Employers should use this information only as a supplement to other information gathered by them and must make independent determination of suitability and completeness of information from all sources to assure proper use of these materials and the safety and health of employees. Any use of this data and information must be determined by the user to be in accordance with applicable federal, state and local laws and regulations.