SAFETY DATA SHEET

Naked Gun VOC Compliant Gun Cleaner

Printed: 04/17/2015
Revision: 04/17/2015

Supersedes Revision: 03/17/2015

Page: 1

1. PRODUCT AND COMPANY IDENTIFICATION

Product Name: Naked Gun VOC Compliant Gun Cleaner

Company Name: W. M. Barr Phone Number:

2105 Channel Avenue (901)775-0100

Memphis, TN 38113

Web site address: www.wmbarr.com

Emergency Contact: 3E 24 Hour Emergency Contact (800)451-8346 **Information:** W.M. Barr Customer Service (800)398-3892

Intended Use: Spray gun cleaning.

Synonyms: CGC112, DGC112, GGC112

Additional Information This product is regulated by the United States Consumer Product Safety Commission

and is subject to certain labeling requirements under the Federal Hazardous Substances Act. These requirements differ from the classification criteria and hazard information required for safety data sheets (SDS). The product label also includes other important information, including directions for use, and should always be read in its entirety prior to

using the product.

2. HAZARDS IDENTIFICATION

Flammable Liquids, Category 2

Serious Eye Damage/Eye Irritation, Category 2

Specific Target Organ Toxicity (single exposure), Category 3

Aspiration Toxicity, Category 2







GHS Signal Word: Danger

GHS Hazard Phrases: H225: Highly flammable liquid and vapor.

H305: May be harmful if swallowed and enters airways.

H319: Causes serious eye irritation.

H336: May cause drowsiness or dizziness.

GHS Precaution Phrases: P210: Keep away from heat/sparks/open flames/hot surfaces. - No smoking.

P233: Keep container tightly closed.

P240: Ground/bond container and receiving equipment.

P241: Use explosion-proof electrical/ventilating/lighting/ equipment.

P242: Use only non-sparking tools.

P243: Take precautionary measures against static discharge.

P261: Avoid breathing gas/mist/vapors/spray. P264: Wash hands thoroughly after handling.

P271: Use only outdoors or in a well-ventilated area.

P280: Wear protective gloves/protective clothing/eye protection/face protection.

P235: Keep cool.

GHS Response Phrases: P301+310: IF SWALLOWED: Immediately call a POISON CENTER or doctor/physician.

P303+361+353: IF ON SKIN (or hair): Remove/take off immediately all contaminated

clothing. Rinse skin with water/shower.

P304+340: IF INHALED: Remove victim to fresh air and keep at rest in a position

comfortable for breathing.

P305+351+338: IF IN EYES: Rinse cautiously with water for several minutes. Remove

contact lenses, if present and easy to do. Continue rinsing.

P312: Call a POISON CENTER or doctor/physician if you feel unwell.

P331: Do NOT induce vomiting.

Licensed to W.M. Barr and Company: MIRS MSDS, (c) A V Systems, Inc.

GHS format

Printed: 04/17/2015 Revision: 04/17/2015

Page: 2

Supersedes Revision: 03/17/2015

P337+313: If eye irritation persists, get medical advice/attention.

P370+378: In case of fire, use dry chemical powder to extinguish.

GHS Storage and Disposal

P403+233: Store container tightly closed in well-ventilated place.

Phrases:

P405: Store locked up.

P501: Dispose of contents/container according to local, state and federal regulations.

Hazard Rating System:





HMIS:

OSHA Regulatory Status:

This material is classified as hazardous under OSHA regulations.

Potential Health Effects (Acute and Chronic):

Inhalation Exposure Effects:

Vapor harmful. High concentrations may lead to central nervous system effects (drowsiness, dizziness, nausea, headaches, paralysis, and loss of consciousness and even death). High vapor concentrations are irritating to the eyes, nose, throat, and

Intentional misuse of this product by deliberately concentrating and inhaling can be harmful or fatal.

Skin Contact Exposure Effects:

Moderately irritating to the skin. Prolonged or repeated contact can result in defatting and drying of the skin which may result in skin irritation and dermatitis (rash).

Eye Contact Exposure Effects:

Contact with the eye may cause moderate to severe irritation.

Ingestion Acute Exposure Effects:

Product may be harmful or fatal if swallowed. Pulmonary aspiration hazard. After ingestion, may enter lungs and produce damage. May produce central nervous system effects, which may include dizziness, loss of balance and coordination, unconsciousness, coma and even death.

Target Organs: Central Nervous System, Respiratory System, Eye, Skin

Primary Routes of Entry: Inhalation, Ingestion

Medical Conditions Generally Diseases of the skin, eyes, and lung (asthma-like conditions).

Aggravated By Exposure:

3. COMPOSITION/INFORMATION ON INGREDIENTS

CAS#	Hazardous Components (Chemical Name)	Concentration	RTECS #
67-64-1	Acetone {2-Propanone}	60.0 -100.0 %	AL3150000
123-86-4	Butyl acetate {n-Butyl acetate. Acetic acid, Butyl	< 5.0 %	AF7350000

Additional Chemical

Specific percentage of composition is being withheld as a trade secret.

Information

Page: 3
Printed: 04/17/2015
Revision: 04/17/2015

Supersedes Revision: 03/17/2015

4. FIRST AID MEASURES

Emergency and First Aid

Procedures:

Inhalation:

If user experiences breathing difficulty, move to air free of vapors, Administer oxygen or

artificial medical assistance can be rendered.

Skin Contact:

Wash with soap and large quantities of water and seek medical attention if irritation from

contact persists.

Eye Contact:

Flush with large quantities of water for at least 15 minutes and seek immediate medical

attention.

Ingestion:

Do not induce vomiting. Call your local poison control center, hospital emergency room

or physician immediately for instructions to induce vomiting.

Signs and Symptoms Of

Exposure:

See Potential Health Effects.

5. FIRE FIGHTING MEASURES

NFPA Class IB

Flash Pt: 0.00 F Method Used: Setaflash Closed Cup (Rapid Setaflash)

Explosive Limits: LEL: 1.7 % UEL: 13 %

Autoignition Pt: No data.

Suitable Extinguishing Media: Use carbon dioxide, dry powder, water spray, or alcohol resistant foam.

Unsuitable Extinguishing

Media:

None known.

Fire Fighting Instructions: Self-contained respiratory protection should be provided for fire fighters fighting fires in

buildings or confined areas. Storage containers exposed to fire should be kept cool with water spray to prevent pressure build-up. Stay away from heads of containers that have

been exposed to intense heat or flame.

Flammable Properties and

Hazards:

Extremely flammable. Vapors are heavier than air and may travel along the ground or may be moved by ventilation and ignited by an ignition source, such as pilot lights, flames, sparks, heaters, smoking, electric motors, static discharge, or other ignition sources at location distant from the material handling point. Product residue can ignite

explosively. Do not weld or cut on empty containers.

6. ACCIDENTAL RELEASE MEASURES

Steps To Be Taken In Case Material Is Released Or Spilled: Vapors may cause flash fire or ignite explosively.

Clean up: Keep unnecessary people away; isolate hazard area and deny entry. Stay upwind, out of low areas, and ventilate closed spaces before entering. Shut off ignition sources; keep flares, smoking or flames out of hazard area. Use non-sparking tools. Use proper bonding and grounding methods for all equipment and processes. Keep out of waterways. Be cautious of vapors collecting in small enclosed spaces, sewers, low lying areas, confined spaces, etc.

Small spills: Take up with sand, earth or other noncombustible absorbent material and place in a plastic container where applicable.

Large spills: Dike far ahead of spill for later disposal.

Licensed to W.M. Barr and Company: MIRS MSDS, (c) A V Systems, Inc.

GHS format

Printed: 04/17/2015 Revision: 04/17/2015

Page: 4

Supersedes Revision: 03/17/2015

Waste Disposal: Dispose in accordance with applicable local, state and federal regulations.

Keep out of drains, sewers, and bodies of water.

7. HANDLING AND STORAGE

Precautions To Be Taken in Handling:

Read carefully all cautions and directions on product label before use. Since empty container retains residue, follow all label warnings even after container is empty. Dispose of empty container according to all regulations. Do not reuse this container.

Do not use this product near any source of heat or open flame, furnace areas, pilot lights, stoves, etc.

Do not use in small enclosed spaces, such as basements and bathrooms. Vapors can accumulate and explode if ignited.

Precautions To Be Taken in Storing:

Keep container tightly closed when not in use. Store in a cool, dry place. Do not store near flames or at elevated temperatures.

8. EXPOSURE CONTROLS/PERSONAL PROTECTION

CAS#	Partial Chemical Name	OSHA TWA	ACGIH TWA	Other Limits
67-64-1	Acetone {2-Propanone}	PEL: 1000 ppm	TLV: 500 ppm STEL: 750 ppm	No data.
123-86-4	Butyl acetate {n-Butyl acetate. Acetic acid. Butyl ester}	PEL: 150 ppm	TLV: 150 ppm STEL: 200 ppm	No data.

Respiratory Equipment (Specify Type):

For OSHA controlled work place and other regular users. Use only with adequate ventilation under engineered air control systems designed to prevent exceeding appropriate TLV.

For occasional use, where engineered air control is not feasible, use properly maintained and properly fitted NIOSH approved respirator for organic solvent vapors. A dust mask does not provide protection against vapors.

Eye Protection: Safety glasses, goggles or face shields are recommended to safeguard against potential

eye contact, irritation, or injury.

Wear gloves with as much resistance to the chemical ingredients as possible. Glove Protective Gloves:

> materials such as natural rubber and neoprene may provide protection. Glove selection should be based on chemicals being used and conditions of use. Consult your glove supplier for additional information. Gloves contaminated with product should be

discarded and not reused.

Various application methods can dictate use of additional protective safety equipment, Other Protective Clothing:

such as impermeable aprons, etc., to minimize exposure.

Engineering Controls (Ventilation etc.):

Use only with adequate ventilation to prevent build-up of vapors. Open all windows and doors. Use only with a cross ventilation of moving fresh air across the work area. If strong odor is noticed or you experience slight dizziness, headache, nausea, or

eye-watering - Stop - ventilation is inadequate. Leave area immediately.

Practices:

Work/Hygienic/Maintenance Wash hands thoroughly after use and before eating, drinking, or smoking.

Do not eat, drink, or smoke in the work area.

Discard any clothing or other protective equipment that cannot be decontaminated.

Licensed to W.M. Barr and Company: MIRS MSDS, (c) A V Systems, Inc. **GHS** format

Printed: 04/17/2015 Revision: 04/17/2015

Page: 5

Supersedes Revision: 03/17/2015

Facilities storing or handling this material should be equipped with an emergency eyewash and safety shower.

O DUVE			DDADEDTI	EC
9. РПТ	SICAL AND (JUCINICAL	PROPERII	

Physical States: [] Gas [X] Liquid [] Solid

Appearance and Odor: Water White / Free and Clear

Melting Point:No data.Boiling Point:131.00 FAutoignition Pt:No data.

Flash Pt: 0.00 F Method Used: Setaflash Closed Cup (Rapid Setaflash)

Explosive Limits: LEL: 1.7 % UEL: 13 %

No data.

Specific Gravity (Water = 1): 0.792

Density: 6.592 LB/GL

Vapor Pressure (vs. Air or

mm Hg):

Vapor Density (vs. Air = 1): > 1 Evaporation Rate: > 1

Solubility in Water: Complete

Percent Volatile: 100.0 % by weight. VOC / Volume: 24.0000 G/L

10. STABILITY AND REACTIVITY

Stability: Unstable [] Stable [X]

Conditions To Avoid -

Instability:

No data available.

Incompatibility - Materials To Strong oxidizing agents.

Avoid:

2-Propanone may form explosive mixtures with chromic anhydride, chromyl alcohol, hexachloromelamine, hydrogen peroxide, permonosulfuric acid, potassium tertbutoxide,

and thioglycol.

Hazardous Decomposition Or Decomposition may produce carbon monoxide, carbon dioxide, and unidentified organic

Byproducts: compounds in black smoke.

Possibility of Hazardous

Will occur []

Will not occur [X]

Reactions:

Conditions To Avoid - No data available.

Hazardous Reactions:

Printed: 04/17/2015 Revision: 04/17/2015

Page: 6

Supersedes Revision: 03/17/2015

11. TOXICOLOGICAL INFORMATION

Toxicological Information: This product has not been tested as a whole. Refer to section 2 for acute and chronic

effects.

CAS# 67-64-1:

Standard Draize Test, Eyes, Species: Rabbit, 20.00 MG, Severe.

Result:

Behavioral: Change in motor activity (specific assay).

Behavioral: Alteration of classical conditioning.

- American Journal of Ophthalmology., Ophthalmic Pub. Co., 435 N. Michigan Ave.,

Suite 1415, Chicago, IL 60611, Vol/p/yr: 29,1363, 1946

CAS#	Hazardous Components (Chemical Name)	NTP	IARC	ACGIH	OSHA
67-64-1	Acetone {2-Propanone}	n.a.	n.a.	A4	n.a.
123-86-4	Butyl acetate {n-Butyl acetate. Acetic acid, Butyl ester}	n.a.	n.a.	n.a.	n.a.

12. ECOLOGICAL INFORMATION

General Ecological

Information:

No information available for this product as a whole.

13. DISPOSAL CONSIDERATIONS

Waste Disposal Method: Dispose of in accordance with all applicable local, state, and federal regulations.

Keep out of sewers and bodies of water.

14. TRANSPORT INFORMATION

LAND TRANSPORT (US DOT):

DOT Proper Shipping Name: Paint Related Material

DOT Hazard Class: 3 FLAMMABLE LIQUID

UN/NA Number: UN1263 Packing Group: II



Additional Transport

Information:

The supplier may apply one of the following exceptions: Combustible Liquid, Consumer Commodity, Limited Quantity, Viscous Liquid, Does Not Sustain Combustion, or others, as allowed under 49CFR Hazmat Regulations. Please consult 49CFR Subchapter C to ensure that subsequent shipments comply with these exceptions.

15. REGULATORY INFORMATION

EPA SARA (Superfund Amendments and Reauthorization Act of 1986) Lists

CAS#	Hazardous Components (Chemical Name)	S. 302 (EHS)	S. 304 RQ	S. 313 (TRI)
67-64-1	Acetone {2-Propanone}	No	Yes 5000 LB	No
123-86-4	Butyl acetate {n-Butyl acetate. Acetic acid, Butyl	No	Yes 5000 LB	No

ester}

This material meets the EPA [X] Yes [] No Acute (immediate) Health Hazard **'Hazard Categories' defined** [] Yes [X] No Chronic (delayed) Health Hazard

for SARA Title III Sections [X] Yes [] No Fire Hazard

311/312 as indicated: [] Yes [X] No Sudden Release of Pressure Hazard

[] Yes [X] No Reactive Hazard

Page: 7
Printed: 04/17/2015
Revision: 04/17/2015

Supersedes Revision: 03/17/2015

CAS # Hazardous Components (Chemical Name) Other US EPA or State Lists

67-64-1 Acetone {2-Propanone} CAA HAP,ODC: No; CWA NPDES: No; TSCA: Yes -

Inventory, 4 Test; CA PROP.65: No

123-86-4 Butyl acetate {n-Butyl acetate. Acetic acid, Butyl CAA HAP,ODC: No; CWA NPDES: Yes; TSCA: Yes -

ster} Inventory, 4 Test; CA PROP.65: No

Regulatory Information:

16. OTHER INFORMATION

Revision Date: 04/17/2015

Preparer Name: W.M. Barr EHS Dept (901)775-0100

Additional Information About No data available.

This Product:

Licensed to W.M. Barr and Company: MIRS MSDS, (c) A V Systems, Inc.

GHS format