**Material Safety Data Sheet** 



# **KLEERMOUNT IN XYLENE**

Revised: 07/13/2010 Replaces: 05/09/2010 Printed: 08/02/2010

# Carolina Biological Supply Company

2700 York Rd | Burlington, NC 27215 • to order: 800.334.5551 • for support: 800.227.1150

## **Section 1 - Product Description**

Product Name: Kleermount in Xylene Product Code(s): 87-1341, 87-1343, 87-1345, 70-0385, 70-0385A, B5995, B5999A, B6007A, B6008, B6010, B6101, B6103, B6103B, B6104, B6104G, B6105, B6107, B6109, B6109A, B6109B, B6109C, B6300, B6310, B6312, BM2010, BM2015, BM2300, BM6010, GEO385, 69-9870, B6090 Size: 7.5 mL, 25 mL, 100 mL, 500 mL Chemical Name: N/A CAS Number: 1330-20-7 **Formula:** See Section 3 Synonyms: N/A Distributor: Carolina Biological Supply Company, 2700 York Road, Burlington, NC 27215 Chemical Information: 800-227-1150 (8am-5pm (ET) M-F) Chemtrec 800-424-9300 (Transportation Spill Response 24 hours)

# Section 2 - Hazard Identification

Emergency Overview: Prolonged exposure may result in allergic reaction. Harmful by inhalation. **Potential Health Effects: Eyes:** May cause irritation. Ingestion: May cause gastrointestinal discomfort.

**Skin:** May cause irritation to skin. Inhalation: May cause irritation to respiratory tract.

# Section 3 - Composition / Information on Ingredients

Principal Hazardous Components: Xylene (CAS# 1330-20-7) 44% TLV units: ACGIH-TLV 100 ppm (TWA) PEL units: OSHA-PEL 100 ppm (TWA)

# **Section 4 - First Aid Measures**

#### **Emergency and First Aid Procedures:**

Eves - In case of contact with eves, rinse immediately with plenty of water and seek medical advice.

Skin - After contact with skin, take off immediately all contaminated clothing, and wash immediately with plenty of ... (Water, unless specified as a water reactive material).

Ingestion - If swallowed, rinse mouth with water (only if the person is conscious). If swallowed, do not induce vomiting: seek

medical advice immediately and show this container or label.

Inhalation - In case of accident by inhalation: remove casualty to fresh air and keep at rest.

#### **Section 5 - Firefighting Procedures**

Flash Point (Method Used): 26.2 C
NFPA Rating:
Health: 2
Fire: 3
Reactivity: 0
Extinguisher Media: Use dry chemical, CO2 or appropriate foam.
Flammable Limits in Air % by Volume: LEL: 1% UEL: 7%
Autoignition Temperature: 463.8 °C
Special Firefighting Procedures: Firefighters should wear full protective equipment and NIOSH approved self-contained breathing apparatus.

Unusual Fire and Explosion Hazards: In use, may form flammable/explosive vapour-air mixture.

Vapours may travel back to ignition source. Closed Containers exposed to heat may explode.

#### **Section 6 - Spill or Leak Procedures**

**Steps to Take in Case Material Is Released or Spilled:** Ventilate area of spill. Eliminate all sources of ignition. Remove all non-essential personnel from area. Clean-up personnel should wear proper protective equipment and clothing. Absorb material with suitable absorbent and containerize for disposal.

#### **Section 7 - Special Precautions**

Precautions to Take in Handling or Storing: Wear suitable protective clothing, gloves and eye/face protection.

Bond and ground containers when transferring liquid.

This material should be kept in an area suitable for the storage of flammable liquids.

Keep container tightly closed in a cool, well-ventilated place.

## **Section 8 - Protection Information**

**Respiratory Protection (Specify Type):** None needed under normal conditions of use with adequate ventilation. A NIOSH/MSHA chemical cartridge respirator should be worn if PEL or TLV is exceeded. **Ventilation:** 

Local Exhaust: Yes Mechanical(General): Yes Special: No Other: No Protective Gloves: Natural rubber, Neoprene, PVC or equivalent. Eye Protection: Splash proof chemical safety goggles should be worn. Other Protective Clothing or Equipment: Lab coat, apron, eye wash, safety shower.

#### **Section 9 - Physical Data**

Molecular Weight: N/A Boiling Point: 58 - 60 °C Vapor Pressure: N/A Vapor Density(Air=1): N/A Percent Volatile by Volume: 44% Solubility in Water: Practically Insoluble Melting Point: N/A

Specific Gravity (H2O=1): N/A Evaporation Rate (BuAc=1): N/A Appearance and Odor: Clear, colorless liquid, Sweet odor.

## Section 10 - Reactivity Data

**Stability:** Stable **Conditions to Avoid:** Heat and sources of ignition. **Incompatibility (Materials to Avoid):** Halogens, Oxidizers, **Hazardous Decomposition Products:** N/A **Hazardous Polymerization:** Will not occur

# Section 11 - Toxicity Data

Toxicity Data: ihl-rat LC50 5000 ppm/4H
orl-rat LD50 4300 mg/kg
Effects of Overexposure:

Acute: See Section 2
Chronic: Not listed as a carcinogen by IARC, NTP or OSHA. Reproductive data cited. Mutation data cited.

Conditions Aggravated by Overexposure: Impaired Kidney Function, Liver disorders, Eye disorders, Skin disorders, Respiratory disorders,
Target Organs: Liver, Kidneys,

Primary Route(s) of Entry: Inhaltion and skin contact.

#### **Section 12 - Ecological Data**

EPA Waste Numbers: U239

#### Section 13 - Disposal Information

**Waste Disposal Methods:** Dispose in accordance with all applicable Federal, State and Local regulations. Always contact a permitted waste disposer (TSD) to assure compliance.

#### **Section 14 - Transport Information**

**DOT Proper Shipping Name:** \*\*\*25 mL bottle is a small quantity exception.\*\*\* UN1307, Description: Xylene solutions, 3, II

#### **Section 15 - Regulatory Information**

**EPA TSCA Status:** On TSCA Inventory **Hazard Category for SARA Section 311/312 Reporting:** Chronic Fire Acute

Name List: Yes **Chemical Category:** No

**CERCLA Section 103 RQ(lb.):** 1,000 **RCRA Section 261.33:** U239

#### **Section 16 - Additional Information**

The information provided in this Material Safety Data Sheet represents a compilation of data drawn directly from various sources available to us. Carolina Biological Supply makes no representation or guarantee as to the suitability of this information to a particular application of the substance covered in the Material Safety Data Sheet. Any employer must carefully assess the

Product Name: KLEERMOUNT IN XYLENE

applicability of any information contained herein in regards to the particular use to which the employer puts the material.

Glossary	
ACGIH	American Conference of Governmental Industrial Hygienists
CAS Number	Chemical Services Abstract Number
CERCLA	Comprehensive Environmental Response, Compensation, and Liability Act
DOT	U.S. Department of Transportation
IARC	International Agency of Research on Cancer
N/A	Not Available
NTP	National Toxicology Program
OSHA	Occupational Safety and Health Administration
PEL	Permissible Exposure Limit
ppm	Parts per million
RCRA	Resource Conservation and Recovery Act
SARA	Superfund Amendments and Reauthorization Act
TLV	Threshold Limit Value
TSCA	Toxic Substances Control Act