



3-IN-ONE.



Safety Data Sheet



1 - Identification

| | |
|---------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Product Name: 3-IN-ONE® Fast-Acting Penetrant Product Use: : Lubricant, Penetrant Restrictions on Use: None identified SDS Date Of Preparation: 4/4/18 | Manufacturer: WD-40 Company Address: 9715 Businesspark Ave. (92131) P.O. Box 80607 San Diego, California, USA 92138 -0607 Telephone: Emergency only: 1-888-324-7596 (PROSAR) Information: 1-888-324-7596 Chemical Spills: 1-800-424-9300 (Chemtrec) 1-703-527-3887 (International Calls) |
|---------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|

2 – Hazards Identification

Hazcom 2012/GHS Classification:

Flammable Liquid Category 4

Aspiration Toxicity Category 1

Skin Irritation Category 2

Specific Target Organ Toxicity Single Exposure Category 3 (nervous system)

Note: This product is a consumer product and is labeled in accordance with the US Consumer Product Safety Commission regulations which take precedence over OSHA Hazard Communication labeling. The actual container label will not include the label elements below. The labeling below applies to industrial/professional products.

Label Elements:**DANGER!**

Combustible Liquid.

May be fatal if swallowed and enters airways.

Causes skin irritation.

May cause drowsiness or dizziness.

Prevention

Keep away from flames and hot surfaces. No smoking.

Avoid breathing vapors.

Wash thoroughly after handling.

Use only outdoors or in a well-ventilated area.

Wear protective gloves.

Response

IF ON SKIN: Wash with plenty of soap and water. If skin irritation occurs: Get medical attention. Take off contaminated clothing and wash it before reuse.

IF INHALED: Remove person to fresh air and keep comfortable for breathing. Call a POISON CENTER or doctor if you feel unwell.

IF SWALLOWED: Immediately call a POISON CENTER or doctor. Do NOT induce vomiting.

In case of fire: Use water fog, dry chemical, carbon dioxide or foam to extinguish.

Storage

Store in a well-ventilated place. Keep cool. Keep container tightly closed.
Store locked up.

Disposal

Dispose of contents and container in accordance with local and national regulations.

3 - Composition/Information on Ingredients

| Ingredient | CAS # | Weight Percent | US Hazcom 2012/ GHS Classification |
|-----------------------------------------------|----------------------------------------|----------------|---------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| LVP Petroleum Distillates, hydrotreated light | 64742-47-8 | 60-80% | Flammable Liquid Category 3 Aspiration Toxicity Category 1 |
| Mineral Spirits | 64742-47-8 64742-88-7 64742-48-9 | 20-30% | Flammable Liquid Category 3 Aspiration Toxicity Category 1 Skin Irritation Category 2 Specific Target Organ Toxicity Single Exposure Category 3 (nervous system) |
| Petroleum Oils | 64742-53-6 64742-56-9 64742-65-0 | 1-5% | Aspiration Toxicity Category 1 |

Note: The exact percentages are a trade secret.

4 – First Aid Measures

Ingestion (Swallowed): Aspiration Hazard. DO NOT induce vomiting. Call physician, poison control center or the WD-40 Safety Hotline at 1-888-324-7596 immediately.

Eye Contact: Flush thoroughly with water. Remove contact lenses if present after the first 5 minutes and continue flushing for several more minutes. Get medical attention if irritation persists.

Skin Contact: Wash with soap and water. If irritation develops and persists, get medical attention.

Inhalation (Breathing): If irritation is experienced, move to fresh air. Get medical attention if irritation or other symptoms develop and persist.

Signs and Symptoms of Exposure: Harmful or fatal if swallowed. If swallowed, may be aspirated and cause lung damage. May cause eye irritation. Causes skin irritation. Vapors may cause drowsiness and drowsiness.

Indication of Immediate Medical Attention/Special Treatment Needed: Immediate medical attention is needed for ingestion.

5 – Fire Fighting Measures

Suitable (and unsuitable) Extinguishing Media: Use water fog, dry chemical, carbon dioxide or foam. Do not use water jet or flooding amounts of water. Burning product will float on the surface and spread fire.

Specific Hazards Arising from the Chemical: Combustible liquid and vapor. Vapors are heavier than air and may travel along surfaces to remote ignition sources and flash back.

Special Protective Equipment and Precautions for Fire-Fighters: Firefighters should always wear positive pressure self-contained breathing apparatus and full protective clothing. Cool fire-exposed containers with water.

6 – Accidental Release Measures

Personal Precautions, Protective Equipment and Emergency Procedures: Wear appropriate protective clothing (see Section 8). Eliminate all sources of ignition and ventilate area.

Methods and Materials for Containment/Cleanup: Contain and collect liquid with an inert absorbent and place in a container for disposal. Clean spill area thoroughly. Report spills to authorities as required.

7 – Handling and Storage

Precautions for Safe Handling: Avoid contact with eyes. Avoid prolonged contact with skin. Avoid breathing vapors or aerosols. Use with adequate ventilation. Keep away from heat, sparks, hot surfaces and open

flames. Wash thoroughly with soap and water after handling. Keep containers closed when not in use. Keep out of the reach of children.

Conditions for Safe Storage: Store in a cool, well-ventilated area, away from incompatible materials. NFPA 30 Class IIIA Liquid.

8 – Exposure Controls/Personal Protection

| Chemical | Occupational Exposure Limits |
|-----------------------------------------------|-----------------------------------------------------------------------------------|
| LVP Petroleum Distillates, hydrotreated light | 1200 mg/m ³ TWA (manufacturer recommended) |
| Mineral Spirits | 100 ppm TWA (manufacturer recommended) |
| Petroleum Oils | 5 mg/m ³ TWA OSHA PEL 5 mg/m ³ (inhalable) TWA ACGIH TLV |

The Following Controls are Recommended for Normal Consumer Use of this Product

Appropriate Engineering Controls: Use in a well-ventilated area.

Personal Protection:

Eye Protection: Avoid eye contact. Safety glasses or goggles recommended.

Skin Protection: Avoid skin contact. Chemical resistant gloves recommended for operations where skin contact is likely.

Respiratory Protection: None needed for normal use with adequate ventilation.

For Bulk Processing or Workplace Use the Following Controls are Recommended

Appropriate Engineering Controls: Use adequate general and local exhaust ventilation to maintain exposure levels below that occupational exposure limits.

Personal Protection:

Eye Protection: Safety goggles recommended where eye contact is possible.

Skin Protection: Wear chemical resistant gloves.

Respiratory Protection: None required if ventilation is adequate. If the occupational exposure limits are exceeded, wear a NIOSH approved respirator. Respirator selection and use should be based on contaminant type, form and concentration. Follow OSHA 1910.134, ANSI Z88.2 and good Industrial Hygiene practice.

Work/Hygiene Practices: Wash with soap and water after handling.

9 – Physical and Chemical Properties

| | | | |
|----------------------------|-------------------------------|-----------------------------------------|------------------------------------------|
| Appearance: | Light brown liquid | Flammable Limits: (Solvent Portion) | LEL: 0.6% UEL: 7.0% |
| Odor: | Mild odor | Vapor Pressure: | 2.6 mmHg @ 68°F (20°C) (mineral spirits) |
| Odor Threshold: | Not established | Vapor Density: | Greater than 1 (air=1) |
| pH: | Not Applicable | Relative Density: | 0.76-0.84 |
| Melting/Freezing Point: | Not established | Solubilities: | Insoluble in water |
| Boiling Point/Range: | >300°F (149°C) | Partition Coefficient; n-octanol/water: | Not established |
| Flash Point: | 141°F (60.6°C) Tag Closed Cup | Autoignition Temperature: | Not established |
| Evaporation Rate: | Not Determined | Decomposition Temperature: | Not established |
| Flammability (solid, gas): | Not applicable | Viscosity: | 1.92 cSt @ 104°F (40°C) |
| VOC: | 188-208 g/L (24.8%) | Pour Point: | -71°F (-57°C) |

10 – Stability and Reactivity

Reactivity: Not reactive under normal conditions

Chemical Stability: Stable

Possibility of Hazardous Reactions: May react with strong oxidizers generating heat.

Conditions to Avoid: Avoid heat, sparks, flames and other sources of ignition.

Incompatible Materials: Strong oxidizing agents.
Hazardous Decomposition Products: Carbon monoxide and carbon dioxide.

11 – Toxicological Information

Symptoms of Overexposure:

Inhalation: High concentrations may cause nasal and respiratory irritation and central nervous system effects such as headache, dizziness and nausea. Intentional abuse may be harmful or fatal.

Skin Contact: Causes skin irritation. Prolonged and/or repeated contact may produce defatting with possible dermatitis.

Eye Contact: Contact may be irritating to eyes. May cause redness and tearing.

Ingestion: This product has low oral toxicity. Swallowing may cause gastrointestinal irritation, nausea, vomiting and diarrhea. This product is an aspiration hazard. If swallowed, can enter the lungs and may cause chemical pneumonitis, severe lung damage and death.

Chronic Effects: None expected.

Carcinogen Status: None of the components are listed as a carcinogen or suspect carcinogen by IARC, NTP, ACGIH or OSHA.

Reproductive Toxicity: None of the components is considered a reproductive hazard.

Numerical Measures of Toxicity:

The oral toxicity of this product is estimated to be greater than 5,000 mg/kg based on an assessment of the ingredients. This product is not classified as toxic by established criteria. It is an aspiration hazard.

12 – Ecological Information

Ecotoxicity: LVP Petroleum Distillates, hydrotreated light: Not expected to be harmful to aquatic organisms, readily biodegradable.

Mineral Spirits: No data available

Persistence and Degradability: LVP Petroleum Distillates, hydrotreated light: Readily biodegradable.

Bioaccumulative Potential: Bioaccumulation is not expected based on an assessment of the ingredients.

Mobility in Soil: No data available

Other Adverse Effects: None known

13 - Disposal Considerations

If this product becomes a waste, it would not be expected to meet the criteria of a RCRA hazardous waste. However, it is the responsibility of the generator to determine at the time of disposal the proper classification and method of disposal. Dispose in accordance with federal, state, and local regulations.

14 – Transportation Information

DOT Surface Shipping Description: Excepted from Hazmat (49CFR 173.150 (F)) in non-bulk packagings.

Bulk Packagings: NA1993, Combustible Liquid, n.o.s. (contains Petroleum Distillates), PG III

IMDG Shipping Description: Not Regulated

ICAO Shipping Description: Not Regulated

NOTE: WD-40 Company does not test containers to assure that they can withstand the pressure change without leakage when transported by air. We do not recommend that our products be transported by air unless a specific review is conducted.

15 – Regulatory Information

U.S. Federal Regulations:

CERCLA 103 Reportable Quantity: This product is not subject to CERCLA reporting requirements, however, oil spills are reportable to the National Response Center under the Clean Water Act and many states have more stringent release reporting requirements. Report spills required under federal, state and local regulations.

SARA TITLE III:

Hazard Category For Section 311/312: Refer to Section 2 for the OSHA Hazard Classification.

Section 313 Toxic Chemicals: This product contains the following chemicals subject to SARA Title III Section 313 Reporting requirements: None

Section 302 Extremely Hazardous Substances (TPQ): None

EPA Toxic Substances Control Act (TSCA) Status: All of the components of this product are listed on the TSCA inventory.

VOC Regulations: This product complies with the consumer product VOC limits of CARB, the US EPA and states adopting the OTC VOC rules.

California Safe Drinking Water and Toxic Enforcement Act (Proposition 65): This product does not contain chemicals regulated under California Proposition 65.

Canadian Environmental Protection Act: One of the components is listed on the NDSL. All of the other ingredients are listed on the Canadian Domestic Substances List or exempt from notification.

16 – Other Information

HMIS Hazard Rating:

Health – 1 (slight hazard), Fire Hazard – 2 (moderate hazard), Physical Hazard – 0 (minimal hazard)

Revision Date: April 4, 2018

Supersedes: July 31, 2014

Revision Summary: Updated section 14 and 15.

Prepared by: Industrial Health & Safety Consultants, Inc. Shelton, CT, USA

Reviewed by: I. Kowalski

Regulatory Affairs Department

1001200/No.0082803