

MATERIAL SAFETY DATA SHEET

SODIUM (I) NITRATE
J.T.BAKER MSDS

Revised: 09/05/00
Replaces: None
Printed: 27/12/01

PRODUCT IDENTIFICATION

PRODUCT NAME: SODIUM NITRATE, CRYSTAL
COMMON SYNONYMS: SODIUM (I) NITRATE; NITRIC ACID, SODIUM SALT; SODA
NITER;
CHILE SALTPETER
CHEMICAL FAMILY: INORGANIC SODIUM COMPOUNDS
FORMULA: NaNO_3
FORMULA WT.: 84.99
CAS NO.: 7631-99-4
NIOSH/RTECS NO.: WC5600000
PRODUCT USE: LABORATORY REAGENT
PRODUCT CODES: 3771, 4501, 3770

CHEMTREC # (800) 424-9300 NATIONAL RESPONSE CENTER # (800) 424-8802
J.T.BAKER INC. 222 RED SCHOOL LANE PHILLIPSBURG, NJ 08865 24-HOUR
EMERGENCY TELEPHONE -- (201) 859-2151

EFFECTIVE: 01/04/94 ISSUED: 04/08/95
REVISION #03

PRECAUTIONARY LABELING

BAKER SAF-T-DATA* SYSTEM

HEALTH	-	1	SLIGHT
FLAMMABILITY	-	0	NONE
REACTIVITY	-	3	SEVERE (OXIDIZER)
CONTACT	-	1	SLIGHT

LABORATORY PROTECTIVE EQUIPMENT

GOGGLES; LAB COAT

U.S. PRECAUTIONARY LABELING

DANGER

CAUSES IRRITATION. HARMFUL IF SWALLOWED OR INHALED. STRONG OXIDIZER.
CONTACT

WITH COMBUSTIBLE MATERIALS, FLAMMABLE MATERIALS, OR POWDERED METALS CAN
CAUSE
FIRE OR EXPLOSION.

KEEP FROM CONTACT WITH CLOTHING AND OTHER COMBUSTIBLE MATERIALS. DO NOT
STORE

NEAR COMBUSTIBLE MATERIALS. AVOID CONTACT WITH EYES, SKIN, CLOTHING.
KEEP IN

TIGHTLY CLOSED CONTAINER. WASH THOROUGHLY AFTER HANDLING. IN CASE OF
FIRE,
SOAK WITH WATER. IN CASE OF SPILL, SWEEP UP AND REMOVE. FLUSH SPILL
AREA
WITH WATER.

PRECAUTIONARY LABELING (CONTINUED)

MATERIAL SAFETY DATA SHEET

SODIUM (I) NITRATE
J.T.BAKER MSDS

Revised: 09/05/00
Replaces: None
Printed: 27/12/01

INTERNATIONAL LABELING

CONTACT WITH COMBUSTIBLE MATERIAL MAY CAUSE FIRE. CAUSES BURNS.
KEEP AWAY FROM HEAT. KEEP AWAY FROM SOURCES OF IGNITION - NO SMOKING.
WEAR
SUITABLE PROTECTIVE CLOTHING, GLOVES AND EYE/FACE PROTECTION.

SAF-T-DATA* STORAGE COLOR CODE: YELLOW (REACTIVE)

COMPONENTS

COMPONENT	CAS NO.	WEIGHT %	OSHA/PEL
ACGIH/TLV			
SODIUM NITRATE	7631-99-4	99-100	N/E N/E

PHYSICAL DATA

BOILING POINT: N/A	VAPOR PRESSURE (MMHG): N/A
MELTING POINT: 306 C (582 F) (AT 760 MM HG)	VAPOR DENSITY (AIR=1): 2.90
SPECIFIC GRAVITY: 2.26 (H2O=1)	EVAPORATION RATE: N/A
SOLUBILITY(H2O): APPRECIABLE (>10%)	% VOLATILES BY VOLUME: 0 (21 C)

PH: N/A

ODOR THRESHOLD (P.P.M.): N/A

PHYSICAL STATE: SOLID

COEFFICIENT WATER/OIL DISTRIBUTION: N/A

APPEARANCE & ODOR: COLORLESS CRYSTALS OR POWDER. ODORLESS.

FIRE AND EXPLOSION HAZARD DATA

FLASH POINT (CLOSED CUP): N/A OXY	NFPA 704M RATING: 0-0-0
--------------------------------------	-------------------------

AUTOIGNITION TEMPERATURE: N/A

FLAMMABLE LIMITS: UPPER - N/A LOWER - N/A

FIRE EXTINGUISHING MEDIA
USE WATER SPRAY.

SPECIAL FIRE-FIGHTING PROCEDURES

FIREFIGHTERS SHOULD WEAR PROPER PROTECTIVE EQUIPMENT AND SELF-
CONTAINED
BREATHING APPARATUS WITH FULL FACEPIECE OPERATED IN POSITIVE
PRESSURE
MODE. MOVE CONTAINERS FROM FIRE AREA IF IT CAN BE DONE WITHOUT RISK.
USE
WATER TO KEEP FIRE-EXPOSED CONTAINERS COOL.

MATERIAL SAFETY DATA SHEET

SODIUM (I) NITRATE
J.T.BAKER MSDS

Revised: 09/05/00
Replaces: None
Printed: 27/12/01

UNUSUAL FIRE & EXPLOSION HAZARDS

STRONG OXIDIZER. CONTACT WITH COMBUSTIBLE MATERIALS, FLAMMABLE MATERIALS,
OR POWDERED METALS CAN CAUSE FIRE OR EXPLOSION. CAN REACT VIOLENTLY WITH
SHOCK, FRICTION OR HEAT.

TOXIC GASES PRODUCED
OXIDES OF NITROGEN

EXPLOSION DATA-SENSITIVITY TO MECHANICAL IMPACT
NONE IDENTIFIED.

EXPLOSION DATA-SENSITIVITY TO STATIC DISCHARGE
NONE IDENTIFIED.

HEALTH HAZARD DATA

THRESHOLD LIMIT VALUE (TLV/TWA): NOT ESTABLISHED

SHORT-TERM EXPOSURE LIMIT (STEL): NOT ESTABLISHED

PERMISSIBLE EXPOSURE LIMIT (PEL): NOT ESTABLISHED

TOXICITY OF COMPONENTS

ORAL RAT LD50 FOR SODIUM NITRATE 1267
MG/KG

ORAL RABBIT LD50 FOR SODIUM NITRATE 2680
MG/KG

CARCINOGENICITY: NTP: NO IARC: NO Z LIST: NO OSHA REG: NO

CARCINOGENICITY
NONE IDENTIFIED.

REPRODUCTIVE EFFECTS
NONE IDENTIFIED.

EFFECTS OF OVEREXPOSURE

INHALATION: IRRITATION OF UPPER RESPIRATORY TRACT, CYANOSIS,
UNCONSCIOUSNESS, HEADACHE, NAUSEA, VOMITING,
DIZZINESS,

WEAKNESS, RAPID INEFFECTIVE BREATHING, LOW BLOOD
PRESSURE, CONVULSIONS

SKIN CONTACT: IRRITATION, PROLONGED CONTACT MAY CAUSE DERMATITIS

EYE CONTACT: IRRITATION

SKIN ABSORPTION: NONE IDENTIFIED

MATERIAL SAFETY DATA SHEET

SODIUM (I) NITRATE
J.T.BAKER MSDS

Revised: 09/05/00
Replaces: None
Printed: 27/12/01

INGESTION: GASTROINTESTINAL IRRITATION, CYANOSIS,
UNCONSCIOUSNESS, HEADACHE, NAUSEA, VOMITING, DIZZINESS, WEAKNESS,
RAPID INEFFECTIVE BREATHING, LOW BLOOD PRESSURE,
CONVULSIONS

CHRONIC EFFECTS: NONE IDENTIFIED

TARGET ORGANS
NONE IDENTIFIED

MEDICAL CONDITIONS GENERALLY AGGRAVATED BY EXPOSURE
NONE IDENTIFIED

PRIMARY ROUTES OF ENTRY
INHALATION, INGESTION, SKIN CONTACT, EYE CONTACT

EMERGENCY AND FIRST AID PROCEDURES

INGESTION: CALL A PHYSICIAN. IF SWALLOWED, IF CONSCIOUS,
IMMEDIATELY INDUCE VOMITING.

INHALATION: IF INHALED, REMOVE TO FRESH AIR. IF NOT BREATHING,
GIVE ARTIFICIAL RESPIRATION. IF BREATHING IS DIFFICULT,
GIVE OXYGEN. PROMPT ACTION IS ESSENTIAL.

SKIN CONTACT: IN CASE OF CONTACT, FLUSH SKIN WITH WATER.

EYE CONTACT: IN CASE OF EYE CONTACT, IMMEDIATELY FLUSH WITH PLENTY
OF WATER FOR AT LEAST 15 MINUTES.

SARA/TITLE III HAZARD CATEGORIES AND LISTS

ACUTE: NO CHRONIC: YES FLAMMABILITY: YES PRESSURE: NO REACTIVITY: NO

EXTREMELY HAZARDOUS SUBSTANCE: NO

CERCLA HAZARDOUS SUBSTANCE: NO

SARA 313 TOXIC CHEMICALS: YES

GENERIC CLASS:

CONTAINS SODIUM NITRATE

GENERIC CLASS REMOVED FROM CFR:

7/1/91

TSCA INVENTORY: YES

REACTIVITY DATA

STABILITY: STABLE
OCCUR

HAZARDOUS POLYMERIZATION: WILL NOT

MATERIAL SAFETY DATA SHEET

SODIUM (I) NITRATE
J.T.BAKER MSDS

Revised: 09/05/00
Replaces: None
Printed: 27/12/01

CONDITIONS TO AVOID: SHOCK, FRICTION, HEAT

INCOMPATIBLES: CYANIDES, COMBUSTIBLE MATERIALS, ORGANIC
MATERIALS,
STRONG REDUCING AGENTS, ALUMINUM

DECOMPOSITION PRODUCTS: OXIDES OF NITROGEN

SPILL & DISPOSAL PROCEDURES

STEPS TO BE TAKEN IN THE EVENT OF A SPILL OR DISCHARGE

WEAR SUITABLE PROTECTIVE CLOTHING. KEEP COMBUSTIBLES (WOOD, PAPER,
OIL,
ETC.) AWAY FROM SPILLED MATERIAL. WITH CLEAN SHOVEL, CAREFULLY
PLACE
MATERIAL INTO CLEAN, DRY CONTAINER AND COVER; REMOVE FROM AREA.
FLUSH
SPILL AREA WITH WATER.

DISPOSAL PROCEDURE

DISPOSE IN ACCORDANCE WITH ALL APPLICABLE FEDERAL, STATE, AND LOCAL
ENVIRONMENTAL REGULATIONS.

EPA HAZARDOUS WASTE NUMBER: D001 (IGNITABLE WASTE)

INDUSTRIAL PROTECTIVE EQUIPMENT

VENTILATION: USE ADEQUATE GENERAL OR LOCAL EXHAUST
VENTILATION TO

KEEP FUME OR DUST LEVELS AS LOW AS POSSIBLE.

RESPIRATORY PROTECTION: NONE REQUIRED WHERE ADEQUATE VENTILATION
CONDITIONS

EXIST. IF AIRBORNE CONCENTRATION IS HIGH, USE
AN
APPROPRIATE RESPIRATOR OR DUST MASK.

EYE/SKIN PROTECTION: SAFETY GOGGLES, BUTYL RUBBER GLOVES ARE
RECOMMENDED.

STORAGE AND HANDLING PRECAUTIONS

SAF-T-DATA* STORAGE COLOR CODE: YELLOW (REACTIVE)

STORAGE REQUIREMENTS

KEEP CONTAINER TIGHTLY CLOSED. STORE SEPARATELY AND AWAY FROM
FLAMMABLE
AND COMBUSTIBLE MATERIALS.

TRANSPORTATION DATA AND ADDITIONAL INFORMATION

DOMESTIC (D.O.T.)

PROPER SHIPPING NAME: SODIUM NITRATE

HAZARD CLASS: 5.1

UN/NA: UN1498

LABELS: 5.1 OXIDIZER

REGULATORY REFERENCES: 49CFR 172.101

PACKAGING GROUP: III

MATERIAL SAFETY DATA SHEET

SODIUM (I) NITRATE
J.T.BAKER MSDS

Revised: 09/05/00
Replaces: None
Printed: 27/12/01

INTERNATIONAL (I.M.O.)

PROPER SHIPPING NAME: SODIUM NITRATE
HAZARD CLASS: 5.1 I.M.O. PAGE: 5180
UN: UN1498 MARINE POLLUTANTS: NO PACKAGING GROUP: III
LABELS: 5.1 OXIDIZING AGENT
REGULATORY REFERENCES: 49CFR PART 176; IMDG CODE

AIR (I.C.A.O.)

PROPER SHIPPING NAME: SODIUM NITRATE
HAZARD CLASS: 5.1 PACKAGING GROUP: III
UN: UN1498
LABELS: 5.1 OXIDIZER
REGULATORY REFERENCES: 49CFR PART 175; ICAO=== WE BELIEVE THE
TRANSPORTATION

FACTUAL AND DATA AND REFERENCES CONTAINED HEREIN TO BE
MEANT AS THE OPINION OF QUALIFIED EXPERTS. THE DATA IS
PRODUCT A GUIDE TO THE OVERALL CLASSIFICATION OF THE
AND IS NOT PACKAGE SIZE SPECIFIC, NOR SHOULD IT
BE TAKEN AS A WARRANTY OR REPRESENTATION FOR WHICH
THE COMPANY ASSUMES LEGAL RESPONSIBILITY.=== THE
CONSIDERATION, INFORMATION IS OFFERED SOLELY FOR YOUR
IN INVESTIGATION, AND VERIFICATION. ANY USE OF THE
LOCAL INFORMATION MUST BE DETERMINED BY THE USER TO BE
49CFR ACCORDANCE WITH APPLICABLE FEDERAL, STATE, AND
TRAINING 49 LAWS AND REGULATIONS. SEE SHIPPER REQUIREMENTS
171.2, CERTIFICATION 172.204, AND EMPLOYEE
CFR 173.1(B).

U.S. CUSTOMS HARMONIZATION NUMBER: 28342900005

NOTE: WHEN HANDLING LIQUID PRODUCTS, SECONDARY PROTECTIVE CONTAINERS MUST BE USED FOR CARRYING. N/A = NOT APPLICABLE, OR NOT AVAILABLE N/E = NOT ESTABLISHED. THE INFORMATION IN THIS MATERIAL SAFETY DATA SHEET MEETS THE REQUIREMENTS OF THE UNITED STATES OCCUPATIONAL SAFETY AND HEALTH ACT AND REGULATIONS PROMULGATED THEREUNDER (29 CFR 1910.1200 ET. SEQ.) AND THE CANADIAN WORKPLACE HAZARDOUS MATERIALS INFORMATION SYSTEM. THIS DOCUMENT IS INTENDED ONLY AS A GUIDE TO THE APPROPRIATE PRECAUTIONARY HANDLING OF THE MATERIAL BY A PERSON TRAINED IN, OR

MATERIAL SAFETY DATA SHEET

SODIUM (I) NITRATE
J.T.BAKER MSDS

Revised: 09/05/00
Replaces: None
Printed: 27/12/01

SUPERVISED BY A PERSON TRAINED IN, CHEMICAL HANDLING. THE USE IS RESPONSIBLE FOR DETERMINING THE PRECAUTIONS AND DANGERS OF THIS CHEMICAL FOR HIS OR HER PARTICULAR APPLICATION. DEPENDING ON USAGE, PROTECTIVE CLOTHIN INCLUDING EYE AND FACE GUARDS AND RESPIRATORS MUST BE USED TO AVOID CONTACT WITH MATERIAL OR BREATHING CHEMICAL VAPORS/FUMES. EXPOSURE TO THIS PRODUCT MAY HAVE SERIOUS ADVERSE HEALTH EFFECTS. THIS CHEMICAL MAY INTERACT WITH OTHER SUBSTANCES. SINCE THE POTENTIAL USES ARE SO VARIED, BAKER CANNOT WARN OF ALL OF THE POTENTIAL DANGERS OF USE OR INTERACTION WITH OTHER CHEMICALS OR MATERIALS. BAKER WARRANTS THAT THE CHEMICAL MEETS THE SPECIFICATIONS SET FORTH ON THE LABEL. BAKER DISCLAIMS ANY OTHER WARRANTIES, EXPRESSED OR IMPLIED, WITH REGARD TO THE PRODUCT SUPPLIED HEREUNDER, ITS MERCHANTABILITY OR ITS FITNESS FOR A PARTICULAR PURPOSE. THE USER SHOULD RECOGNIZE THAT THIS PRODUCT CAN CAUSE SEVERE INJURY AND EVE DEATH, ESPECIALLY IF IMPROPERLY HANDLED OR THE KNOWN DANGERS OF USE ARE NOT HEDED. READ ALL PRECAUTIONARY INFORMATION. AS NEW DOCUMENTED GENERAL SAFETY INFORMATION BECOMES AVAILABLE, BAKER WILL PERIODICALLY REVISE THIS MATERIAL SAFETY DATA SHEET. NOTE: CHEMTREC, CANUTEC, AND NATIONAL RESPONSE CENTER EMERGENCY TELEPHONE NUMBERS ARE TO BE USED ONLY IN THE EVENT OF CHEMICAL EMERGENCIES INVOLVING A SPILL, LEAK, FIRE, EXPOSURE, OR ACCIDENT INVOLVING CHEMICALS. ALL NON-EMERGENCY QUESTIONS SHOULD BE DIRECTED TO CUSTOMER SERVICE (1-800-JTBAKER ASSISTANCE. COPYRIGHT 1995 J.T.BAKER INC. * TRADEMARKS OF J.T.BAKER INC. APPROVED BY QUALITY ASSURANCE DEPARTMENT.