

Liquid Drain Opener

Safety Data Sheet



SECTION 1: Product and company identification

Product name : Liquid Drain Opener
Use of the substance/mixture : Drain maintainer
Product code : 025501
Company : Share Corporation
P.O. Box 245013
Milwaukee, WI 53224 - USA
T (414) 355-4000
Emergency number : Chemtrec: (800) 424-9300

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

Classification (GHS-US)

Acute Tox. 3 (Oral) H301
Acute Tox. 4 (Dermal) H312
Skin Corr. 1A H314

Full text of H-phrases: see section 16

2.2. Label elements

GHS-US labeling

Hazard pictograms (GHS-US)



GHS05



GHS06

Signal word (GHS-US)

: Danger

Hazard statements (GHS-US)

: Toxic if swallowed
Harmful in contact with skin
Causes severe skin burns and eye damage

Precautionary statements (GHS-US)

: Do not breathe mist, vapors
Wash thoroughly after handling
Do not eat, drink or smoke when using this product
Wear eye protection, protective gloves, protective clothing
If swallowed: Immediately call a doctor, a POISON CENTER
If swallowed: rinse mouth. Do NOT induce vomiting
If on skin: Wash with plenty of water
If on skin (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower
If inhaled: Remove person to fresh air and keep comfortable for breathing
If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing
Immediately call a POISON CENTER, a doctor
Call a doctor, a POISON CENTER if you feel unwell
Rinse mouth
Take off contaminated clothing and wash it before reuse
Wash contaminated clothing before reuse
Store locked up
Dispose of contents/container to comply with local/regional/national/international regulations.

2.3. Other hazards

No additional information available

2.4. Unknown acute toxicity (GHS US)

Not applicable

SECTION 3: Composition/information on ingredients

3.1. Substance

Not applicable

Full text of H-phrases: see section 16

3.2. Mixture

Liquid Drain Opener

Safety Data Sheet



Name	Product identifier	%	Classification (GHS-US)
sodium hydroxide, caustic soda	(CAS No) 1310-73-2	40 - 70	Acute Tox. 4 (Dermal), H312 Skin Corr. 1A, H314
potassium hydroxide, caustic potash	(CAS No) 1310-58-3	7 - 13	Met. Corr. 1, H290 Acute Tox. 3 (Oral), H301 Skin Corr. 1A, H314

SECTION 4: First aid measures

4.1. Description of first aid measures

- First-aid measures general : If you feel unwell, seek medical advice (show the label where possible).
- First-aid measures after inhalation : Remove victim to fresh air and keep at rest in a position comfortable for breathing.
- First-aid measures after skin contact : Take off immediately all contaminated clothing and wash it before reuse. Rinse skin with water/shower. Take victim to a doctor if irritation persists.
- First-aid measures after eye contact : Remove contact lenses, if present and easy to do. Continue rinsing. Rinse cautiously with water for several minutes. Immediately call a poison center or doctor/physician.
- First-aid measures after ingestion : Immediately call a poison center or doctor/physician. Rinse mouth. Do NOT induce vomiting.

4.2. Most important symptoms and effects, both acute and delayed

- Symptoms/injuries : Causes severe skin burns and eye damage.
- Symptoms/injuries after inhalation : Corrosive to the respiratory tract.
- Symptoms/injuries after skin contact : Harmful in contact with skin. Caustic burns/corrosion of the skin.
- Symptoms/injuries after eye contact : Causes serious eye damage. Permanent eye damage.
- Symptoms/injuries after ingestion : Toxic if swallowed. Burns to the gastric/intestinal mucosa.

4.3. Indication of any immediate medical attention and special treatment needed

No additional information available

SECTION 5: Firefighting measures

5.1. Extinguishing media

- Suitable extinguishing media : ABC powder.

5.2. Special hazards arising from the substance or mixture

- Reactivity : Reacts violently with water. Reacts with (some) metals: release of highly flammable gases/vapours (hydrogen).

5.3. Advice for firefighters

- Firefighting instructions : Exercise caution when fighting any chemical fire. Use water moderately and if possible collect or contain it. Use water spray or fog for cooling exposed containers.
- Protection during firefighting : Do not enter fire area without proper protective equipment, including respiratory protection.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

- General measures : Isolate from fire, if possible, without unnecessary risk.

6.1.1. For non-emergency personnel

- Protective equipment : Gloves. Protective goggles. Face-shield.
- Emergency procedures : Keep upwind.

6.1.2. For emergency responders

- Protective equipment : Equip cleanup crew with proper protection.
- Emergency procedures : Stop leak if safe to do so. Stop release. Ventilate area.

6.2. Environmental precautions

Avoid release to the environment. Prevent soil and water pollution.

6.3. Methods and material for containment and cleaning up

- For containment : Contain released substance, pump into suitable containers.
- Methods for cleaning up : Absorb spillage to prevent material damage. Small quantities of liquid spill: neutralize with acid solution. This material and its container must be disposed of in a safe way, and as per local legislation.

6.4. Reference to other sections

No additional information available

Liquid Drain Opener

Safety Data Sheet



SECTION 7: Handling and storage

7.1. Precautions for safe handling

- Precautions for safe handling : Carry operations in the open/under local exhaust/ventilation or with respiratory protection. Do not handle until all safety precautions have been read and understood. Use personal protective equipment as required.
- Hygiene measures : Do not eat, drink or smoke when using this product. Wash contaminated clothing before reuse.

7.2. Conditions for safe storage, including any incompatibilities

- Storage conditions : Keep container closed when not in use. Store in original container. Store in a dry place. Store in a closed container. Keep cool.
- Incompatible products : strong acids.
- Incompatible materials : Metals.
- Storage area : Keep only in the original container. Store in a dry area. Store in a cool area.

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

No additional information available

8.2. Exposure controls

- Personal protective equipment : Face shield. Gloves. Safety glasses. Protective clothing. Use appropriate personal protective equipment when risk assessment indicates this is necessary.



SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

- Physical state : Liquid
- Appearance : Clear to hazy liquid.
- Odor : Mild odor
- Odor threshold : No data available
- pH : 14
- Melting point : No data available
- Freezing point : No data available
- Boiling point : No data available
- Flash point : No data available
- Relative evaporation rate (butyl acetate=1) : No data available
- Flammability (solid, gas) : No data available
- Explosion limits : No data available
- Explosive properties : No data available
- Oxidizing properties : No data available
- Vapor pressure : No data available
- Relative density : No data available
- Relative vapor density at 20 °C : No data available
- Specific gravity / density : 1.48 g/ml
- Solubility : Soluble in water.
- Log Pow : No data available
- Log Kow : No data available
- Auto-ignition temperature : No data available
- Decomposition temperature : No data available
- Viscosity : No data available
- Viscosity, kinematic : No data available
- Viscosity, dynamic : No data available
- VOC content : 0 %

Liquid Drain Opener

Safety Data Sheet



SECTION 10: Stability and reactivity

10.1. Reactivity

Reacts violently with water. Reacts with (some) metals: release of highly flammable gases/vapours (hydrogen).

10.2. Chemical stability

No additional information available

10.3. Possibility of hazardous reactions

Reacts violently with water.

10.4. Conditions to avoid

No additional information available

10.5. Incompatible materials

May be corrosive to metals. strong acids. Metals.

10.6. Hazardous decomposition products

May release flammable gases.

SECTION 11: Toxicological information

11.1. Information on toxicological effects

Acute toxicity : Oral: Toxic if swallowed. Dermal: Harmful in contact with skin.

Drain Away	
LD50 oral rat	214 mg/kg Potassium Hydroxide
LD50 dermal rabbit	1350 mg/kg Sodium Hydroxide
sodium hydroxide, caustic soda (1310-73-2)	
LD50 oral rat	4090 mg/kg
LD50 dermal rabbit	1350 mg/kg
ATE CLP (oral)	4090.000 mg/kg body weight
ATE CLP (dermal)	1350.000 mg/kg body weight
potassium hydroxide, caustic potash (1310-58-3)	
LD50 oral rat	214 mg/kg
ATE CLP (oral)	500.000 mg/kg body weight

Skin corrosion/irritation	: Causes severe skin burns and eye damage. pH: 14
Serious eye damage/irritation	: Not classified pH: 14
Respiratory or skin sensitization	: Not classified
Germ cell mutagenicity	: Not classified
Carcinogenicity	: Not classified
Reproductive toxicity	: Not classified
Specific target organ toxicity (single exposure)	: Not classified
Specific target organ toxicity (repeated exposure)	: Not classified
Aspiration hazard	: Not classified
Symptoms/injuries after inhalation	: Corrosive to the respiratory tract.
Symptoms/injuries after skin contact	: Harmful in contact with skin. Caustic burns/corrosion of the skin.
Symptoms/injuries after eye contact	: Causes serious eye damage. Permanent eye damage.
Symptoms/injuries after ingestion	: Toxic if swallowed. Burns to the gastric/intestinal mucosa.

SECTION 12: Ecological information

12.1. Toxicity

No additional information available

12.2. Persistence and degradability

No additional information available

Liquid Drain Opener

Safety Data Sheet



12.3. Bioaccumulative potential

No additional information available

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Waste disposal recommendations : Dispose of contents/container to comply with local/regional/national regulations.

SECTION 14: Transport information

Department of Transportation (DOT)

UN-No.(DOT) : UN3266
Proper Shipping Name (DOT) : Corrosive liquid, basic, inorganic, n.o.s. (sodium hydroxide, potassium hydroxide)
Transport hazard class(es) (DOT) : 8 - Class 8 - Corrosive material 49 CFR 173.136
Hazard labels (DOT) : 8 - Corrosive



Packing group (DOT) : II - Medium Danger
DOT Packaging Non Bulk (49 CFR 173.xxx) : 202
DOT Packaging Bulk (49 CFR 173.xxx) : 242
DOT Symbols : G - Identifies PSN requiring a technical name
DOT Special Provisions (49 CFR 172.102) : B2,IB2,T11,TP2,TP27
DOT Packaging Exceptions (49 CFR 173.xxx) : 154
DOT Quantity Limitations Passenger aircraft/rail (49 CFR 173.27) : 1 L
DOT Quantity Limitations Cargo aircraft only (49 CFR 175.75) : 30 L
DOT Vessel Stowage Location : B
DOT Vessel Stowage Other : 40 - Stow "clear of living quarters", 52 - Stow "separated from" acids

Additional information

Other information : This product may be eligible to be shipped as a Consumer Commodity ORM-D utilizing the exception found at 49 CFR 173.154.

ADR

No additional information available

Transport by sea

No additional information available

Air transport

No additional information available

SECTION 15: Regulatory information

All components of this product are listed, or excluded from listing, on the United States Environmental Protection Agency Toxic Substances Control Act (TSCA) inventory.

This product or mixture does not contain a toxic chemical or chemicals in excess of the applicable de minimis concentration as specified in 40 CFR §372.38(a) subject to the reporting requirements of section 313 of Title III of the Superfund Amendments and Reauthorization Act of 1986 and 40 CFR Part 372.

sodium hydroxide, caustic soda (1310-73-2)	
Not listed on SARA Section 313 (Specific toxic chemical listings)	
RQ (Reportable quantity, section 304 of EPA's List of Lists)	1000 lb

Liquid Drain Opener

Safety Data Sheet



potassium hydroxide, caustic potash (1310-58-3)

Not listed on SARA Section 313 (Specific toxic chemical listings)

RQ (Reportable quantity, section 304 of EPA's List of Lists) 1000 lb

California Proposition 65 - This product contains, or may contain, trace quantities of a substance(s) known to the state of California to cause cancer and/or reproductive toxicity

SECTION 16: Other information

Training advice : Normal use of this product shall imply use in accordance with the instructions on the packaging.


Full text of H-phrases:

Acute Tox. 3 (Oral)	Acute toxicity (oral) Category 3
Acute Tox. 4 (Dermal)	Acute toxicity (dermal) Category 4
Met. Corr. 1	Corrosive to metals Category 1
Skin Corr. 1A	Skin corrosion/irritation Category 1A
H290	May be corrosive to metals
H301	Toxic if swallowed
H312	Harmful in contact with skin
H314	Causes severe skin burns and eye damage

NFPA health hazard : 3 - Short exposure could cause serious temporary or residual injury even though prompt medical attention was given.

NFPA fire hazard : 0 - Materials that will not burn.

NFPA reactivity : 1 - Normally stable, but can become unstable at elevated temperatures and pressures or may react with water with some release of energy, but not violently.



Prepared by: Technical Department

This information is based on our current knowledge and is intended to describe the product for the purposes of health, safety and environmental requirements only. It should not therefore be construed as guaranteeing any specific property of the product. No warranty is expressed or implied regarding the accuracy of this data or the results obtained from the use thereof. Our company assumes no responsibility for personal injury or property damage to the vendee, users or third parties caused by the material. Such vendees or users assume all risks associated with the use of this material.