Product Name: Adhesion Promoter

Product identifier: 100883 Revision Date: 08-18-2016

Replaces:



1. Identification

Product identifier used on the label:

Product Name: Adhesion Promoter

Product identifier: 100883

Other means of identification

Synonyms: No data available

Chemical Family: ALCOHOL

Recommended use of the chemical and restrictions on

use:

Name, address, and telephone number of the chemical manufacturer, importer, or other responsible party

Chemical Manufacturer / **ITW Evercoat**

Importer / Distributor: a division of Illinois Tool Works Inc.

> 6600 Cornell Road Cincinnati, OH 45242

ADHESION PROMOTER

513-489-7600

Emergency phone number: CHEMTREC: 1-800-424-9300

CANUTEC: 1-613-996-6666

2. Hazard(s) identification

Classification of the chemical in accordance with paragraph (d) of §1910.1200;

GHS Hazard Symbols:





GHS Classification: Flammable Liquid Category 1

Germ Cell Mutagenicity Category 1B

Carcinogenicity Category 1A

Skin Corrosion/Irritation Category 2

Serious Eye Damage/Eye Irritation Category 2A

Reproductive Toxicity Category 2

Specific Target Organ Systemic Toxicity (STOT) - Repeated Exposure Category 2

Hazardous to the aquatic environment - Acute Category 2

Specific Target Organ Systemic Toxicity (STOT) - Single Exposure Category 3

Hazardous to the aquatic environment - Chronic Category 3

Page 1 of 11

Product Name: Adhesion Promoter

Product identifier: 100883 Revision Date: 08-18-2016

Replaces:

GHS Signal Word: Danger

GHS Hazard Statements: Extremely flammable liquid and vapour.

Causes skin irritation.

Causes serious eye irritation. May cause drowsiness or dizziness.

May cause genetic defects.

May cause cancer.

Suspected of damaging fertility or the unborn child.

May cause damage to organs through prolonged or repeated exposure.

Toxic to aquatic life.

Harmful to aquatic life with long lasting effects.

GHS Precautionary Statements: Safety Precautions:

Obtain special instructions before use.

Do not handle until all safety precautions have been read and understood. Keep away from heat/sparks/open flames/hot surfaces. – No smoking.

Ground/bond container and receiving equipment.

Use explosion-proof electrical/ventilating/lighting equipment.

Use only non-sparking tools.

Take precautionary measures against static discharge. Do not breathe dust/fume/gas/mist/vapours/spray. Avoid breathing dust/fume/gas/mist/vapours/spray.

Wash thoroughly after handling.

Use only outdoors or in a well-ventilated area.

Avoid release to the environment.

Wear protective gloves/protective clothing/eye protection/face protection.

First Aid Measures: IF ON SKIN: Wash with plenty of soap and water.

IF ON SKIN (or hair): Remove/Take off immediately all contaminated clothing.

Rinse skin with water/shower.

IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable

for breathing.

IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses,

if present and easy to do. Continue rinsing.

IF exposed or concerned: Get medical advice/attention. Call a POISON CENTER or doctor/physician if you feel unwell.

Get medical advice/attention if you feel unwell.

Specific treatment (see on this label).

If skin irritation occurs: Get medical advice/attention. If eye irritation persists: Get medical advice/attention. In case of fire: Use appropriate media to extinguish.

Storage: Store in a well-ventilated place. Keep container tightly closed.

Store in a well-ventilated place. Keep cool.

Store locked up.

Disposal: Dispose of contents/container in accordance with

local/regional/national/international regulation for hazardous wastes.

Product Name: Adhesion Promoter

Product identifier: 100883 Revision Date: 08-18-2016

Replaces:

Hazards not otherwise

No data available

classified:

3. Composition/information on ingredients					
Chemical Component:	CAS number and other unique identifiers	% (or range) of ingredient			
Toluene	108-88-3	30 - 60			
Acetone	67-64-1	7 - 15			
Isobutane	75-28-5	5 - 10			
Isobutyl Acetate	110-19-0	5 - 10			
Propane	74-98-6	5 - 10			
Xylene	1330-20-7	1 - 5			
n-Butyl alcohol	71-36-3	1 - 5			
Isopropyl Alcohol	67-63-0	1 - 5			
Ethylbenzene	100-41-4	0.1 - 1			

The specific chemical identity and/or exact percentage (concentration) of composition has been withheld as a trade secret.

4. First-aid measures

Description of necessary measures, subdivided according to the different routes of exposure, i.e., inhalation, skin and eye contact, and ingestion:

Fue Camback	Inches adjustative florida access with a planeture for out an extraord 20 majoritae	
Eve Contact:	Immediately flush eyes with plenty of water for at least 20 minutes	

retracting eyelids often. Tilt the head to prevent chemical from transferring to the uncontaminated eye. Get immediate medical attention and monitor the eye daily as advised by your physician. Flush eyes gently with water for at least 15 minutes, lifting upper &

lower eye lids. Seek medical advice if symptoms persist

Skin Contact: Wash with soap and water. Remove contaminated clothing and

launder. Get medical attention if irritation develops or persists. Wash affected area thoroughly with soap and water. Seek medical advice if symptoms persist Remove contaminated clothing and continue flushing with water. Wash clothing before reuse. Remove to fresh air. If breathing is difficult, have a trained

Inhalation: Remove to fresh air. If breathing is difficult, have a trained individual administer oxygen. If not breathing, give artificial

respiration and have a trained individual administer oxygen. Get medical attention immediately. If inhaled, remove victim from exposure to a well-ventilated area. If breathing becomes labored or other symptoms develop, seek medical attention at once. Keep the

victim warm and quiet.

Ingestion: Corrosive. Do not induce vomiting! Drink one glass of water

followed by milk if available. Seek medical attention immediately and give the medical care provider with this MSDS. Do not induce

Product Name: Adhesion Promoter

Product identifier: 100883 Revision Date: 08-18-2016

Replaces:

vomiting unless directed to do so by medical personnel. Seek immediate medical attention. Aspiration of material into the lungs can cause chemical pneumonitis which can be fatal.

Most important symptoms/effects, acute and delayed:

Most important

Most important

No data available

symptoms/effects (Acute):

No data available

symptoms/effects (Delayed):

Indication of immediate medical attention and special treatment

No additional first aid information available

needed, if necessary:

5. Fire-fighting measures

Suitable (and unsuitable) extinguishing media:

Suitable extinguishing media: Use alcohol resistant foam, carbon dioxide, or dry chemical

extinguishing agents. Water spray or fog may also be effective for extinguishing if swept across the base of the fire. Water can also be used to absorb heat and keep exposed material from being

damaged by fire. Carbon dioxide Dry chemical Alcohol foam Water

foa

Unsuitable extinguishing media: No data available

Specific hazards arising from the chemical (e.g., nature of any hazardous combustion products):

Fire and/or Explosion

Hazards:

Vapors may be ignited by heat, sparks, flames or other sources of ignition at or above the low flash point giving rise to a Class B fire. Vapors are heavier than air and may travel to a source of ignition and flash back Do not expose container to heat, flame, sparks or

other sources of ignition.

Do not place in hot water or near radiators, stoves or other sources

of heat.

Do not subject aerosol cans to impact.

Closed containers may explode when exposed to extreme heat.

Hazardous Combustion

Products:

Hydrocarbons, Smoke, Carbon monoxide

Special protective equipment and precautions for fire-

fighters:

Do not enter fire area without proper protection including selfcontained toxic breathing apparatus and full protective equipment. Fight fire from a safe distance and a protected location due to the potential of hazardous vapors and decomposition products.

Flammable component(s) of this material may be lighter than water and burn while floating on the surface. Use water spray/fog for cooling. In case of large fire cool containers with water jet in order

Product Name: Adhesion Promoter

Product identifier: 100883 **Revision Date:** 08-18-2016

Replaces:

to prevent pressure buildup, auto ignition or explosion.

Avoid spreading burning liquid with water used to cool containers. Do not enter fire area without proper protection including self-contained breathing apparatus and full protective equipment.

6. Accidental release measures

Personal precautions, protective equipment, and emergency procedures: Exposure to the spilled material may be irritating or harmful. Follow personal protective equipment recommendations found in Section VIII of this MSDS. Additional precautions may be necessary based on special circumstances created by the spill including; the material spilled, the quantity of the spill, the area in which the spill occurred. Also consider the expertise of employees in the area responding to the spill.

Methods and materials for containment and cleaning up:

Prevent the spread of any spill to minimize harm to human health and the environment if safe to do so. Wear complete and proper personal protective equipment following the recommendation of Section VIII at a minimum. Dike with suitable absorbent material like granulated clay. Gather and store in a sealed container pending a waste disposal evaluation. Do not use combustible materials such as sawdust as an absorbent. Activate available exhaust ventilation equipment in the immediate spill area. Keep away from heat. Use an inert absorbent such as sand or vermiculite. Place in properly labeled closed container.

7. Handling and storage

Precautions for safe handling: Harmful or irritating material. Avoid contacting and avoid breathing

the material. Use only in a well ventilated area. Do not use in presence of open flame, sparks or ignition sources. Keep away from heat. Avoid breathing vapors or mists. Do not get in eyes, on skin

and clothing Wash thoroughly after handling

Conditions for safe storage, including any incompatibilities

Conditions for safe storage: Store in a cool dry ventilated location. Isolate from incompatible

materials and conditions. Keep container(s) closed. Store in a cool dry place Keep away from heat, sparks, and flame Store away from sources of heat and light. Do not puncture or incinerate. Store in a

cool, well ventilated area not to exceed 50 deg c.

Materials to Avoid/Chemical

Incompatibility:

Strong oxidizing agents Strong acids Strong alkalies

Product Name: Adhesion Promoter

Product identifier: 100883 **Revision Date:** 08-18-2016

Replaces:

8. Exposure controls/personal protection

OSHA permissible exposure limit (PEL), American Conference of Governmental Industrial Hygienists (ACGIH) Threshold Limit Value (TLV), and any other exposure limit used or recommended by the chemical manufacturer, importer, or employer preparing the safety data sheet, where available:

Chemical Component	OSHA PEL	ACGIH TLV-TWA	ACGIH STEL
Toluene	100 ppm	100 ppm	No data available
Acetone	1000 ppm	500 ppm	750 ppm
Isobutane	No data available	1000 ppm	No data available
Isobutyl Acetate	150 ppm	150 ppm	No data available
Propane	1000 ppm	2500 ppm	No data available
Xylene	100 ppm	100 ppm	150 ppm
n-Butyl alcohol	100 ppm	No data available	No data available
Isopropyl Alcohol	400 ppm	400 ppm	No data available
Ethylbenzene	100 ppm	100 ppm	125 ppm

Appropriate engineering controls:

Local exhaust ventilation or other engineering controls are normally required when handling or using this product to avoid overexposure. General or local ventilation or isolation may prove adequate to keep airborne exposures below exposure limits. Explosion proof exhaust ventilation should be used.

Individual protection measures, such as personal protective equipment:

Eye Protection:

Wear chemically resistant safety glasses with side shields when handling this product. Wear additional eye protection such as chemical splash goggles and/or face shield when the possibility exists for eye contact with splashing or spraying liquid, or airborne material. Do not wear contact lenses. Have an eye wash station available. Splash proof chemical goggles are recommended to protect against the splash of product.

Skin Protection:

Wear protective gloves. Inspect gloves for chemical break-through and replace at regular intervals. Clean protective equipment regularly. Wash hands and other exposed areas with mild soap and water before eating, drinking, and when leaving work. Protective gloves and proper clothing should be worn to prevent skin contact. Gloves should be made of neoprene or natural rubber. To prevent repeated or prolonged skin contact, wear impervious clothing and boots

Respiratory Protection:

Respiratory protection will be required when handling this product. Use respirators only if ventilation cannot be used to eliminate symptoms or reduce the exposure to below acceptable levels. Use a NIOSH approved respirator designed to remove particulate matter and organic solvent vapors. NIOSH approved air purifying respirator with organic vapor cartridge and HEPA filter. Air purifying respirators should not be used in oxygen deficient or IDLH

Product Name: Adhesion Promoter

Product identifier: 100883 Revision Date: 08-18-2016

Replaces:

atmospheres

Other Protective Equipment: Splash proof chemical goggles are recommended to protect against

the splash of product. Protective gloves and proper clothing should

be worn to prevent skin contact. Gloves should be made of

neoprene or natural rubber. To prevent repeated or prolonged skin

contact, wear impervious clothing and boots

9. Physical and chemical properties

Appearance (physical state, color, etc.):

Appearance (physical state): Liquid Color: Clear Odor: Ketone

Odor threshold:

pH:

No data available

No data available

No data available

No data available

Initial Boiling Point and Boiling Range (°C): -42 Flash Point (°C): -18

Evaporation Rate:No data available
Flammability (solid, gas):
No data available

Upper/lower flammability or explosive limits:
Upper Flammable/Explosive Limit (%): 12.8
Lower Flammable/Explosive Limit (%): 1.1

Vapor Pressure:No data available

Vapor Density: > 1

Relative Density:Solubility(ies):
Not determined
Complete; 100%

Partition coefficient: n-octanol/water: 2.76 2.36

Auto-ignition Temperature (°C):No data availableDecomposition Temperature:No data availableViscosity:No data available

10. Stability and reactivity

Reactivity: No data available

Chemical stability: Stable under normal conditions.

Possibility of hazardousNo data available

reactions:

Conditions to avoid (e.g., static Sources of ignition discharge, shock, or vibration): Open flames

Sparks Heat

Incompatible materials: Strong oxidizing agents Strong acids Strong alkalies

Hazardous decomposition Carbon dioxide Carbon monoxide Sulfur containing gases Hydrogen

Product Name: Adhesion Promoter

Product identifier: 100883 Revision Date: 08-18-2016

Replaces:

products: sulfide Irritating fumes

11. Toxicological information

Information on the likely routes

Eye contact, Skin contact, Absorption, Ingestion

of exposure (inhalation,

ingestion, skin and eye contact):

Symptoms related to the

No data available

physical, chemical and toxicological characteristics:

Delayed and immediate effects and also chronic effects from short- and long-term exposure:

Immediate (Acute) Health Effects by Route of Exposure:

Inhalation Irritation: Can cause severe respiratory irritation, dizziness, weakness, fatigue, nausea,

headache and possible unconsciousness. Headache, dizziness, nausea, and loss of

coordination are indications of excessive exposure to vapors or spray mists

Inhalation Toxicity: Harmful! Can cause systemic damage (see "Target Organs)

Skin Contact: Can cause moderate skin irritation, defatting, and dermatitis. Not likely to cause

permanent damage.

Skin Absorption: Harmful if absorbed through the skin. May cause severe irritation and systemic

damage. Contact with skin can cause irritation, (minor itching, burning and /or redness), Dermatitis, Defatting may be readily absorbed through the skin. Contact

may cause irritation and possible dermatitis or sensitization.

Eye Contact: Can cause severe irritation. Eye contact may result in corneal injury. Symptoms may

include discomfort or pain, excess blinking and tear production, with marked redness and swelling of the conjunctiva. Temporary vision impairment (cloudy or

blurred vision) is possible. Can cause irritation.

Ingestion Irritation: Corrosive to tissue. Can cause severe and permanent damage to mouth, throat,

stomach. Aspiration may lead to lung damage. Can burn mouth, throat, and stomach. Causes gastrointestinal tract irritation, nausea, vomiting, diarrhea and

possible ulcerations to mucous membranes.

Ingestion Toxicity: Harmful if swallowed. May cause systemic poisoning.

Long-Term (Chronic) Health Effects:

Carcinogenicity: May cause cancer. The IARC has classified ethyl benzene as a group 2B carcinogen

(possibly carcinogenic to humans) based on the increase of kidney tumors in rats

and an increase in lung and liver cancer in mice.

Reproductive and

Suspected of damaging fertility or the unborn child.

Developmental Toxicity:

Mutagenicity: May cause genetic defects.

Inhalation: Upon prolonged and/or repeated exposure, can cause severe respiratory irritation,

dizziness, weakness, fatigue, nausea, headache and possible unconsciousness. Harmful! Can cause systemic damage upon prolonged and/or repeated exposure

(see "Target Organs)

Skin Contact: Upon prolonged or repeated contact, can cause moderate skin irritation, defatting,

Product Name: Adhesion Promoter

Product identifier: 100883 Revision Date: 08-18-2016

Replaces:

and dermatitis. Not likely to cause permanent damage.

Skin Absorption: Upon prolonged or repeated exposure, harmful if absorbed through the skin. May

cause severe irritation and systemic damage.

Numerical measures of toxicity (such as acute toxicity estimates) Component Toxicology Data

Chemical Component	Oral LD50	Dermal LD50	Inhalation LC50
Toluene	Oral LD50 Rat 5000 mg/kg		Inhalation LC50 (4h) Rat 4000 ppm
Acetone	Oral LD50 Rat 5800 mg/kg	Dermal LD50 Rabbit 20000 mg/kg	Inhalation LC50 (4h) Rat > 16000 ppm
Isobutyl Acetate	Oral LD50 Rat 13400 mg/kg		
Xylene	Oral LD50 Rat 4300 mg/kg		Inhalation LC50 (4h) Rat 5000 ppm
n-Butyl alcohol	Oral LD50 Rat 790 mg/kg		Inhalation LC50 (4h) Rat 8000 ppm
Ethylbenzene	Oral LD50 Rat 3500 mg/kg		

Whether the hazardous chemical is listed in the National Toxicology Program (NTP) Report on Carcinogens (latest edition) or has been found to be a potential carcinogen in the International Agency for Research on Cancer (IARC) Monographs (latest edition), or by OSHA

Chemical Name	OSHA Carcinogen	IARC Carcinogen	NTP Carcinogen	
No data available	N	N	N	

12. Ecological information

Ecotoxicity (aquatic and terrestrial, where available):

Toxic to aquatic life. Toxic to aquatic life with long lasting effects. This material is toxic to aquatic organisms and should not be released to

sewage, draining systems or any body of water exceeding

concentrations of approved limits under applicable regulations and

permits.

Persistence and degradability:

No data available

Bioaccumulative potential:

No data

Mobility in soil: Other adverse effects (such as No data available No data available

hazardous to the ozone layer):

Ecological Toxicity Data

Chemical Component	Aquatic EC50 Crustacea	Aquatic ERC50 Algae	Aquatic LC50 Fish
Acetone	Aquatic EC50 (48h)		Aquatic LC50 (96h)
	Daphnia 10294 - 17704		Rainbow Trout 4740 -

Product Name: Adhesion Promoter

Product identifier: 100883 Revision Date: 08-18-2016

Replaces:

	MG/L	6330 MG/L
n-Butyl alcohol	Aquatic EC50 (48h)	Aquatic LC50 (96h) 100
-	Daphnia 1897 - 2072	- 500 MG/L
	MG/L	
Xylene		Aquatic LC50 (96h)
-		7.711 - 9.591 MG/L
Ethylbenzene	Aquatic EC50 (48h)	Aquatic LC50 (96h) 7.5
	Daphnia 1.37 - 4.4 MG/L	- 11 MG/L

13. Disposal considerations

Description of waste residues and information on their safe handling and methods of disposal, including the disposal of any contaminated packaging

Description of waste residues:Spent or discarded material is a hazardous waste.
Disposal must be in accordance with applicable Federal,

State/Provincial and Local regulations.

Waste treatment methods Dispose of by incineration following Federal, State, Local, or

(including packaging): Provincial regulations.

Waste Disposal Code(s): D001

14. Transport information

UN number: UN1950 **UN proper shipping name**: AEROSOLS

Transport hazard class(es): 2

Packing group: No data available

The shipper is responsible for following all applicable regulations. The transportation classification provided is based on ITW Evercoat original packaging, which is suitable for domestic ground transport only.

15. Regulatory information

Safety, health and environmental regulations specific for the product in question

TSCA Status: The intentional ingredients of this product are listed.

Regulated Components

Chemical Component	CAS number and other unique identifiers	CERCLA	SARA EHS	SARA 313	California Prop 65
Toluene	108-88-3	N	N	Υ	Υ
Acetone	67-64-1	N	N	Υ	N
n-Butyl alcohol	71-36-3	N	N	Υ	N
Xylene	1330-20-7	N	N	Υ	N

Product Name: Adhesion Promoter

Product identifier: 100883 Revision Date: 08-18-2016

Replaces:

Ethylbenzene	100-41-4	N	N	Υ	Υ	

16. Other information, including date of preparation or last revision.

Revision Date: 08-18-2016

Revision Number: 10

Disclaimer: NOTICE: The information accumulated herein is believed to be correct as of the date issued from sources, which are believed to be accurate and reliable. Since it is not possible to anticipate all circumstances of use, recipients are advised to confirm, in advance of need, that the information is current, applicable and suitable to their circumstances