

DEFT INC -- 071, 23BR2 DEFTOIL MEDIUM WALNUT -- 8010-00N031630

=====  
Product Identification  
=====

Product ID:071, 23BR2 DEFTOIL MEDIUM WALNUT

MSDS Date:06/20/1989

FSC:8010

NIIN:00N031630

MSDS Number: BPLMB

=== Responsible Party ===

Company Name:DEFT INC

Address:17451 VON KARMAN AVE

City:IRVINE

State:CA

ZIP:92714

Country:US

Info Phone Num:714-470-0400

Emergency Phone Num:714-470-0400

CAGE:33458

=== Contractor Identification ===

Company Name:DEFT INC

Address:17451 VON KARMAN AVE

City:IRVINE

State:CA

ZIP:92714-6205

Country:US

Phone:800 424-9300

CAGE:33458

Company Name:DEFT, INC.

Address:17451 VON KARMAN AVE

City:IRVINE

State:CA

ZIP:92614

Country:US

Phone:949-474-0400

CAGE:33461

=====  
Composition/Information on Ingredients  
=====

Ingred Name:MINERAL SPIRITS. VP: 5

CAS:64742-88-7

Fraction by Wt: 60%

OSHA PEL:500 PPM (MFR)

ACGIH TLV:100 PPM (MFR)

Ingred Name:SOLVENT NAPHTHA (PETROLEUM), LIGHT AROMATIC; (C8&10  
AROMATIC HYDROCARBON). VP: 3

CAS:64742-95-6

Fraction by Wt: <5%

OSHA PEL:100 PPM

ACGIH TLV:100 PPM

Ingred Name:FIRST AID PROC: VOMIT. DO NOT GIVE ANYTHING BY MOUTH TO AN  
UNCON PERSON. OBTAIN MED ATTN.

RTECS #:9999999ZZ

Ingred Name:OTHER PREC:HAVE BEEN READ/UNDERSTOOD. SMOKE IN SMOKING

AREAS ONLY.  
RTECS #:9999999ZZ  
Other REC Limits:NONE SPECIFIED

Ingrd Name:VENT:REMOVE ALL IGNITION SOURCES (HEAT, SPARKS, FLAMES-HOT SURFACES).  
RTECS #:9999999ZZ  
Other REC Limits:NONE SPECIFIED

==== Hazards Identification =====

LD50 LC50 Mixture:NONE SPECIFIED BY MANUFACTURER.  
Routes of Entry: Inhalation:YES Skin:YES Ingestion:YES  
Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO  
Health Hazards Acute and Chronic:ACUTE: VAP ARE IRRITATING TO EYES/NOSE/ THROAT. INHAL MAY CAUSE HDCH/DFCLT BRTHG & LOSS OF CONSCIOUSNESS. CHRONIC: PRLNG CONT WILL CAUSE DRYING & CRACKING OF SKIN, DUE TO DEFAT ACTION. SKIN SENSIT, AS THMA/OTHER ALLERGIC RESPONSES MAY DEVELOP. INHAL: IRRIT OF RESP TRACT & ACUTE NERV SYS DEPRESS CHARACT BY(EFTS OF OVEREX  
Explanation of Carcinogenicity:NOT RELEVANT  
Effects of Overexposure:HLTH HAZ:FOLLOW PROGRESSIVE STEPS: HDCH, DIZZ, STAGGER GAIT, CONFUSN, UNCON/COMA. SKIN: CONT CAN CAUSE IRRIT. SYMP MAY BE SWELL/RED, & RASH. EYES:LIQ, AEROSOLS/VAP ARE IRRITATING & MAY CAUSE TEAR/RED, & SWELL ACCOMPANIED BY STINGING SENSATION. SKIN ABSORP: PRLNG/ RPTD CONT CAN CAUSE MOD IRRIT, DRY, & DEFAT OF(SUPP DATA  
Medical Cond Aggravated by Exposure:ASTHMA AND ANY OTHER RESPIRATORY DISORDERS. SKIN ALLERGIES, ECZEMA, AND DERMATITIS.

==== First Aid Measures =====

First Aid:INHAL:MOVE TO AN AREA FREE FROM RISK OF FURTHER EXPOS. RESTORE BRTHG. ASTHMATIC TYPE SYMP MAY DEVELOP & MAY BE IMMED/DELAYED BY SEVERAL HRS. OBTAIN MED ATTN. SKIN:REMOVE CONTAMD CLTHG. WASH AFFECTED A REAS THORO W/SOAP/H2O. WASH CONTAMD CLTHG THORO BEFORE REUSE. EYES: FLUSH W/CLEAN LUKEWARM H2O (LOW PRESS) FOR @ LST 15 MIN, OCCAS LIFTING LIDS. OBTAIN MED ATTN. INGEST: DO NOT INDUCE (ING 3)

==== Fire Fighting Measures =====

Flash Point Method:TCC  
Flash Point:105F,41C  
Lower Limits:1%  
Extinguishing Media:FOAM, ALCOHOL FOAM, CO2, DRY CHEMICAL, WATER FOG.  
Fire Fighting Procedures:WEAR NIOSH/MSHA APPRVD SCBA & FULL PROT EQUIP. WATER MAY BE USED TO COOL CLSD CONTR TO PREVENT PRESSURE BUILD-UP, AUTOIGNIT OR EXPLOSION.  
Unusual Fire/Explosion Hazard:KEEP CONTR TIGHTLY CLSD. ISOLATE FROM HEAT/ SPARKS, ELEC EQUIP & OPEN FLAMES. CLSD CONTR MAY EXPLODE WHEN EXPOS TO EXTREME HEAT. APPLICATN TO HOT SURF(SUPP DATA

==== Accidental Release Measures =====

Spill Release Procedures:EVACUATE ALL NON-ESSNTL PERS. REMOVE ALL SOURCES OF IGNIT (FLAME, SPARK SOURCES, HOT SURF). VENT AREA.

CONTAIN & REMOVE WITH INERT ABSORB & NON-SPARKING TOOLS.  
Neutralizing Agent:NONE SPECIFIED BY MANUFACTURER.

=====  
===== Handling and Storage =====

Handling and Storage Precautions:STORE IN BLDGS DESIGNED TO COMPLY  
W/OSHA 1910.106. AVOID STORING NEAR HIGH TEMP, FIRE, OPEN FLAMES, &  
SPARK SOURCES. STORE IN TIGHTLY CLSD CONTR.  
Other Precautions:STORE IN WELL VENTD AREAS. KEEP CONTR TIGHT & UPRIGHT  
TO PVNT LEAKEAGE. PVNT PRLNG BRTHG OF VAP/SPRAY MISTS. PRLNG  
OVEREXP MAY CAUSE AN ALLERGIC RXN. AVOID CONT W/SKIN/EYES. DO NOT  
TAKE INTERNALLY. DO NOT HNDLE UNTIL MFR SFTY PREC (ING 4)

=====  
===== Exposure Controls/Personal Protection =====

Respiratory Protection:NIOSH/MSHA APPRVD RESP THAT IS RECOM FOR USE IN  
AN ORG VAP ENVIRON (AIR PURIFYING/FRESH AIR SUPPLIED) IS NEC.  
OBSERVE OSHA REGS FOR RESP USE. VENTILATION SHOULD BE PROVIDED TO  
KEEP EXPOSURE LEVELS BEL OW OSHA PERMISSIBLE LIMITS.  
Ventilation:EXHAUST VENT SUFFICIENT TO KEEP AIRBORNE CONC OF SOLV VAP/  
MISTS BELOW THEIR RESPECTIVE TLV'S MUST BE UTILIZED. (ING 5)  
Protective Gloves:NEOPRENE, RUBBER, POLYETHYLENE.  
Eye Protection:CHEM WORK GOG OR FULL LNGTH FSHLD.  
Other Protective Equipment:USE LONG SLEEVE AND LONG LEG CLOTHING.  
REMOVE AND WASH CONTAMINATED CLOTHING BEFORE REUSE.  
Work Hygienic Practices:WASH HANDS BEFORE EATING, SMOKING, OR USING  
WASHROOM.

Supplemental Safety and Health

EXPLO HAZ: REQ SPECIAL PREC. DURING EMER CNDTNS OVEREXP TO DECOMP PROD  
MAY CAUSE HLTH HAZ. SYMP MAY NOT BE IMMED APPARENT. EFTS OF  
OVEREXP: SKIN WHICH CAN CAUSE SKIN TO CRACK. INGEST: CAN RSLT IN  
IRRI T & POSS CORR ACTION IN MOUTH, STOM TISSUE & DIGESTIVE TRACT.  
VOMIT MAY CAUSE ASPIR OF SOLV, RSLTG IN CHEM PNEUMIT.

=====  
===== Physical/Chemical Properties =====

HCC:F4  
Boiling Pt:B.P. Text:306F,152C  
Vapor Pres:SEE INGRED  
Vapor Density:HVR/AIR  
Spec Gravity:0.9  
Evaporation Rate & Reference:0.1(N-BUTYL ACETATE)  
Appearance and Odor:BROWN LIQUID WITH SOLVENT ODOR.  
Percent Volatiles by Volume:64.5

=====  
===== Stability and Reactivity Data =====

Stability Indicator/Materials to Avoid:YES  
STRONG OXIDIZING AGENTS.  
Stability Condition to Avoid:HIGH TEMPERATURES, SPARKS, OR OPEN FLAMES.  
Hazardous Decomposition Products:BY HIGH HEAT/TEMPERATURE: CO, CO2, AND  
NOX.

=====  
===== Disposal Considerations =====

Waste Disposal Methods:WASTE MUST BE DISPOSED OF I/A/W FED, ST, & LOC  
ENVIRONMENTAL CTL REGS. EMPTY CONTR MUST BE HANDLED W/CARE, DUE TO

PROD RESIDUE & FLAMMABLE VAPOR. DO NOT INCINERATE CLOSED  
CONTAINERS.

Disclaimer (provided with this information by the compiling agencies):  
This information is formulated for use by elements of the Department  
of Defense. The United States of America in no manner whatsoever,  
expressly or implied, warrants this information to be accurate and  
disclaims all liability for its use. Any person utilizing this  
document should seek competent professional advice to verify and  
assume responsibility for the suitability of this information to their  
particular situation.