

V
L
M

MATERIAL SAFETY

P. O. BOX 391 - ASHLAND, KENTUCKY 41101 - (606) 324-3333

DATA SHEET

24-HOUR-EMERGENCY TELEPHONE (606) 324-1133

000100

AUTOMATIC TRANSMISSION FLUID TYPE FA

PAGE: 1

THIS MSDS COMPLIES WITH 29 CFR 1910.1200 (THE HAZARD COMMUNICATION STANDARD)

PRODUCT NAME: AUTOMATIC TRANSMISSION FLUID TYPE FA

NAPA DETROIT
ATTN: MIKE OBIERSHEA
30550 E. CORSE
ROMULUS, MI 48179

08 86 022 0104312-012
DATA SHEET NO: 0102025-001
LATEST REVISION DATE: 12/89-04352
PRODUCT:
INVOICE: REGST
INVOICE DATE: 02/20/86
TO:

SECTION I-PRODUCT IDENTIFICATION

GENERAL OR GENERIC ID: PETROLEUM BASED-LUBRICATING OIL
DOT HAZARD CLASSIFICATION: NOT APPLICABLE

SECTION II-COMPONENTS

INGREDIENT	% (BY WT)	PEL	TLV	MG/M3	NOTE
PETROLEUM LUBE OIL	>60	5	5	MG/M3	(1)
CAS #: 64742-65-0					

(1): PEL/TLV IS FOR OIL MIST.

SECTION III-PHYSICAL DATA

PROPERTY	REFINEMENT	MEASUREMENT
BOILING POINT	FOR COMPONENT(>60 %)	> 425.00 DEG F (218.33 DEG C) 2 760.00 MMHG
VAPOR PRESSURE	FOR COMPONENT(10-30%)	< 5.00 MMHG (68.00 DEG F (20.00 DEG C)
SPECIFIC VAPOR DENSITY	AIR = 1	> 1.0
SPECIFIC GRAVITY		.880 (60.00 DEG F (15.55 DEG C)
PERCENT VOLATILES	NOT APPLICABLE	
EVAPORATION RATE		SLOWER THAN ETHER

SECTION IV-FIRE AND EXPLOSION INFORMATION

FLASH POINT(COC) 390.00 DEG F
(198.88 DEG C)

EXPLOSIVE LIMIT (PRODUCT) LOWER - 1.1%

EXTINGUISHING MEDIA: REGULAR FOAM OR CARBON DIOXIDE OR DRY CHEMICAL

HAZARDOUS DECOMPOSITION PRODUCTS: MAY FORM TOXIC MATERIALS: CARBON DIOXIDE AND CARBON MONOXIDE, PHOSPHOROUS COMPOUNDS, NITROGEN COMPOUNDS, ZINC OXIDE, ETC.

FIREFIGHTING PROCEDURES: WEAR SELF-CONTAINED BREATHING APPARATUS WITH A FULL FACEPIECE OPERATED IN PRESSURE-DEMAND OR OTHER POSITIVE PRESSURE MODE WHEN FIGHTING FIRES.

WATER OR FOAM MAY CAUSE FROTHING WHICH CAN BE VIOLENT AND POSSIBLY ENDANGER THE LIFE OF THE FIREFIGHTER, ESPECIALLY IF SPRAYED INTO CONTAINERS OF HOT, BURNING LIQUID.

SPECIAL FIRE & EXPLOSION HAZARDS: NEVER USE WELDING OR CUTTING TORCH ON OR NEAR DRUM (EVEN EMPTY) BECAUSE PRODUCT (EVEN JUST RESIDUE) CAN IGNITE EXPLOSIVELY.

NFPA CODES: HEALTH- 1 FLAMMABILITY- 1 REACTIVITY- 0

SECTION V-HEALTH HAZARD DATA

PERMISSIBLE EXPOSURE LEVEL: NOT ESTABLISHED FOR PRODUCT. SEE SECTION II.
EFFECTS OF ACUTE OVEREXPOSURE: FOR COMPONENT

EYES - CAN CAUSE MODERATE IRRITATION, REDNESS, TEARING.
SKIN - CAN CAUSE SLIGHT IRRITATION.
SWALLOWING - CAN CAUSE GASTROINTESTINAL IRRITATION, NAUSEA, VOMITING, AND DIARRHEA.
BREATHING - MIST CAN CAUSE DAMAGE TO NASAL AND RESPIRATORY PASSAGES.

FIRST AID:

IF ON SKIN: THOROUGHLY WASH EXPOSED AREA WITH SOAP AND WATER. REMOVE CONTAMINATED CLOTHING. LAUNDRY CONTAMINATED CLOTHING BEFORE RE-USE.

IF IN EYES: FLUSH WITH LARGE AMOUNTS OF WATER, LIFTING UPPER AND LOWER LIDS

**MATERIAL SAFETY
DATA SHEET**

24-HOUR-EMERGENCY-TELEPHONE (606) 324-1133

000100

AUTOMATIC TRANSMISSION FLUID TYPE PA

PAGE 2

SECTION V-HEALTH HAZARD DATA (CONTINUED)

OCCASIONALLY, GET MEDICAL ATTENTION.

IF SWALLOWED: IMMEDIATELY DRINK TWO GLASSES OF WATER AND INDUCE VOMITING BY EITHER GIVING IPECAC SYRUP OR BY PLACING FINGER AT BACK OF THROAT. NEVER GIVE ANYTHING BY MOUTH TO AN UNCONSCIOUS PERSON. GET MEDICAL ATTENTION IMMEDIATELY.

IF BREATHED: REMOVE INDIVIDUAL TO FRESH AIR.

SECTION VI-REACTIVITY DATA

HAZARDOUS POLYMERIZATION: CANNOT OCCUR

STABILITY: STABLE

INCOMPATIBILITY: AVOID CONTACT WITH: STRONG OXIDIZING AGENTS.

SECTION VII-SPILL OR LEAK PROCEDURES

STEPS TO BE TAKEN IN CASE MATERIAL IS RELEASED OR SPILLED:

SMALL SPILL: ABSORB LIQUID ON PAPER, VERMICULITE, FLOOR ABSORBENT, OR OTHER ABSORBENT MATERIAL AND TRANSFER TO HOOD.

LARGE SPILL: ELIMINATE ALL IGNITION SOURCES (FLARES, FLAMES INCLUDING PILOT LIGHTS, ELECTRICAL SPARKS). PERSONS NOT WEARING PROTECTIVE EQUIPMENT SHOULD BE EXCLUDED FROM AREA OF SPILL UNTIL CLEAN-UP HAS BEEN COMPLETED. STOP SPILL AT SOURCE, DIKE AREA OF SPILL TO PREVENT SPREADING, PUMP LIQUID TO SALVAGE TANK. REMAINING LIQUID MAY BE TAKEN UP ON SAND, CLAY, EARTH, FLOOR ABSORBENT, OR OTHER ABSORBENT MATERIAL AND SHOVELED INTO CONTAINERS. PREVENT RUN-OFF TO SEWERS, STREAMS OR OTHER BODIES OF WATER. IF RUN-OFF OCCURS, NOTIFY PROPER AUTHORITIES AS REQUIRED, THAT A SPILL HAS OCCURED.

WASTE DISPOSAL METHOD:

SMALL SPILL: ALLOW VOLATILE PORTION TO EVAPORATE IN HOOD. ALLOW SUFFICIENT TIME FOR VAPORS TO COMPLETELY CLEAR HOOD DUCT WORK. DISPOSE OF REMAINING MATERIAL IN ACCORDANCE WITH APPLICABLE REGULATIONS.

LARGE SPILL: DESTROY BY LIQUID INCINERATION. CONTAMINATED ABSORBENT MAY BE DEPOSITED IN A LANDFILL IN ACCORDANCE WITH LOCAL, STATE AND FEDERAL REGULATIONS.

SECTION VIII-PROTECTIVE EQUIPMENT TO BE USED

RESPIRATORY PROTECTION: IF TLV OF THE PRODUCT OR ANY COMPONENT IS EXCEEDED, A NIOSH/MSHA JOINTLY APPROVED AIR SUPPLIED RESPIRATOR IS ADVISED IN ABSENCE OF PROPER ENVIRONMENTAL CONTROL. OSHA REGULATIONS ALSO PERMIT OTHER NIOSH/MSHA RESPIRATORS UNDER SPECIFIED CONDITIONS. (SEE YOUR SAFETY EQUIPMENT SUPPLIER). ENGINEERING OR ADMINISTRATIVE CONTROLS SHOULD BE IMPLEMENTED TO REDUCE EXPOSURE.

VENTILATION: PROVIDE SUFFICIENT MECHANICAL (GENERAL AND/OR LOCAL EXHAUST) VENTILATION TO MAINTAIN EXPOSURE BELOW TLV(S).

PROTECTIVE GLOVES: WEAR RESISTANT GLOVES SUCH AS: NEOPRENE

EYE PROTECTION: CHEMICAL SPLASH GOGGLES IN COMPLIANCE WITH OSHA REGULATIONS ARE ADVISED; HOWEVER, OSHA REGULATIONS ALSO PERMIT OTHER TYPE SAFETY GLASSES. (CONSULT YOUR SAFETY EQUIPMENT SUPPLIER)

OTHER PROTECTIVE EQUIPMENT: TO PREVENT REPEATED OR PROLONGED SKIN CONTACT, WEAR IMPERVIOUS CLOTHING AND BOOTS.

SECTION IX-SPECIAL PRECAUTIONS OR OTHER COMMENTS

CONTAINERS OF THIS MATERIAL MAY BE HAZARDOUS WHEN EMPTIED. SINCE EMPTIED CONTAINERS RETAIN PRODUCT RESIDUES (VAPOR, LIQUID, AND/OR SOLID), ALL HAZARD PRECAUTIONS GIVEN IN THIS DATASHEET MUST BE OBSERVED.

THE SPECIFIC CHEMICAL IDENTITY HAS BEEN WITHHELD AS A TRADE SECRET.

THE INFORMATION ACCUMULATED HEREIN IS BELIEVED TO BE ACCURATE BUT IS NOT WARRANTED TO BE WHETHER ORIGINATING WITH THE COMPANY OR NOT. RECIPIENTS ARE ADVISED TO CONFIRM IN ADVANCE OF NEED THAT THE INFORMATION IS CURRENT, APPLICABLE, AND SUITABLE TO THEIR CIRCUMSTANCES.